NOTES: REVISIONS THIRD ANGLE PROJ. 🕀 🖯 REV DESCRIPTION DATE I. MATERIALS AND FINISHES: RELEASE TO MFG 08-Aug-19 BODY - STAINLESS STEEL, PASSIVATED CONTACT - BERYLLIUM COPPER, GOLD PLATING 5. ORDERING INFORMATION: INSULATOR - PTFE A. ADDITIONAL CANDLESTICK LENGTHS ARE AVAILABLE B. CHANGE XXX TO DESIRED CONTACT PROJECTION AND 2. ELECTRICAL: YYY TO DESIRED INSULATOR PROJECTION LENGTH IN INCHES A. IMPEDANCE: 50 OHM [.705 MAX. CONTACT PROJECTION, .100 MIN. CONTACT PROJECTION] C. EXAMPLE: 901-IPBI00000AE HAS CONTACT PROJECTION OF .100 [2.54] B. FREQUENCY RANGE: DC - 18 GHz C. VSWR(RETURN LOSS): 1.15 (-23 dB), MAX. AND NO INSULATOR PROJECTION, D. DIELECTRIC WITHSTANDING VOLTAGE: 1000 VRMS, MIN. AS SHOWN IN "VIEW A" 901-IPB705590AM HAS CONTACT PROJECTION OF .705 [17.91] AND INSULATOR PROJECTION OF .590 [14.99], A. DURABILITY: 500 CYCLES MIN. AS SHOWN IN "VIEW B" B. TEMPERATURE RANGE: -65° C TO +165° C D. CONTACT AMPHENOL RF MARKETING FOR QUOTE AND MORE INFORMATION 4. PACKAGING: A. QUANTITY: SINGLE PACK B. MARKING: PACKAGING TO BE MARKED "AMPHENOL RF. PART NUMBER, AND DATE CODE" .375 REF - 🗌 " A " -[9.53] .065 REF □ "B" [1.65] [17.91] PART NUMBERS ENDING IN "E"-PART NUMBERS ENDING IN "M"-CONTACT PROJECTION HAVE EPOXY CAPTIVATION HAVE STAKED CAPTIVATION - .590 [14.99] 100 INSULATOR PROJECTION [2.54] TAB LENGTH .005 Ø.102 REF [0.13][2.59] TAB THICKNESS TYP(4) $-\emptyset.050$ [1.27] TAB WIDTH Ø.625 REF VIEW A VIEW B [15.88] 901-IPBI00000AE SHOWN 901-IPB705590AM SHOWN DRAWING NO. "A" IN [MM] "B" IN [MM] CAPTIVATION 901-IPBXXXYYYAF .375 [9.53] .250 [6.35] FPOXY 901-IPBXXXYYYAM .375 [9.53] .250 [6.35] MECHANICAL 901-2PBXXXYYYAE .500 [12.70] .340 [8.64] EPOXY

CUSTOMER OUTLINE DRAWING

ECO

12523

 $\emptyset.050$

- —Ø . 163

[1.27]

[4.|4]

APPR

CJV

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE:

2 PLACE DECIMAL
3 PLACE DECIMAL
ANGLES
±.015 (0,381 mm) ±.005 (0,127 mm) ± 1°

.340 [8.64]

.375 [9.53]

.375 [9.53]

.689 [17.50]

.689 [17.50]

MECHANICAL

EPOXY

MECHANICAL

EPOXY

MECHANICAL

NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

.500 [12.70]

.687 [17.45]

.687 [17.45]

1.000 [25.40]

1.000 [25.40]

901-2PBXXXYYYAM

901-3PBXXXYYYAE

901-3PBXXXYYYAM

901-4PBXXXYYYAE

90I-4PBXXXYYYAM

N	MATERIAL SEE NOTES	DRAWN B. GREENBAUM	DATE 26-Oct-17	T Sm
		ENGINEER B. GREENBAUM	DATE 26-Oct-17	ST
	REFERENCE	APPROVED	DATE	
	EAR: 7643 REF: 901-9215-3CCSF	K. CAPOZZI	08 - Aug - 19	SCAL
	ONFIGURATION LEVEL: In Work	CAD FILE		
F	FINISH			

TITLE SMA PANEL JACK, TAB		Amp	phenol RF
STEEL BODY PASSIVATE VARIOUS LENGTHS	D	www.amphenolrf.com	
		DRAWING NO.	90 I - XPB X X X Y Y Y A X
CALE: 5.0:1.0 SHEET 2 DWG SIZE	OF 2 REV	ITEM NO.	90 I - XPB X X X Y Y Y A X
R		PART NO.	90I-XPBXXXYYYAX