## 24 INCHES LENGTH



Connector A 132114 SMA Plug Straight Brass Gold + Heatshrink 50 Ohm RG-316 Continuity/Hi-Pot Connector B 112234 BNC Jack Straight Bulkhead - Rear Mount Brass Nickel

## Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

| Γ   | Connector A       |                  |  | Cable                                |                   |                              | Connector B           |   |  |
|---|-------------------|------------------|--|--------------------------------------|-------------------|------------------------------|-----------------------|---|--|
| F   | Part #:           | 132114           |  | Part #:                              | RG-316            | Part #:                      | 112234                |   |  |
|   | Description:      | SMA PLUG RG17    | 74 RG316 LMR100 500  | Description:                         | RG-316 - ST 0.102 | Description:                 | BNC Clamp BHD Jk      | ( RG188 500   |  |
| т   | Гуре:             | SMA              |  | Dielectric:                          | ST                | Туре:                        | BNC                   |   |  |
|   | Gender:           | Plug             |  | Shielding:                           | Braid             | Gender:                      | Jack                  |   |  |
| E   | Body Type:        | Straight         |  | Diameter:                            | 0.102             | Body Type:                   | Straight              |   |  |
| c   | Contact Type:     | Solder           |  | Impedance:                           | 50 Ohm            | Contact Type:                | Crimp                 |   |  |
| F   | Polarity:         | Standard         |  | Sheathing:                           | None              | Polarity:                    | Standard              |   |  |
| 1   | mpedance:         | 50 Ohm           |  | Testing:                             | Continuity Hi-Pot | Impedance:                   | 50 Ohm                |   |  |
| N   | Nounting:         | Cable            |  | Length:                              | 24 Inches         | Mounting:                    | Bulkhead - Rear Mo    | unt   |  |
|   | Body Material:    | Brass            |  | , s                                  |                   | Body Material:               | Brass                 |   |  |
|   | Body Finish:      | Gold             |  |                                      |                   | Body Finish:                 | Nickel                |   |  |
|   | P Rating:         | None             |  |                                      |                   | IP Rating:                   | None                  |   |  |
|   | Contact Material: | Brass            |  |                                      |                   | Contact Material:            | Beryllium Copper      |   |  |
|   | Contact Finish:   | Gold             |  |                                      |                   | Contact Finish:              | Silver                |   |  |
|   | Max. Freq.:       | 12.4 GHz         |  |                                      |                   | Max. Freq.:                  | 4 GHz                 |   |  |
|   | Booting:          | SMA Plug Straigh | ıt   |                                      |                   | Booting:                     | BNC Jack Straight BHD |   |  |
|   | <b>-</b>          |                  |  |                                      |                   | Clocking:                    | 0°                    |   |  |
| THIS DRAWING MAY CONTAIN<br>PROPRIETA INVIDENTATION |                   |                  |  | Title:                               | ST 112 C216 241   |                              | UNLESS SPECIFIED      |   |  |
| FOR ANY PURPOSE DET<br>INC. IT MAY NOT BE RE        |                   |                  | PROPRIETARY INFORMATION A<br>FOR ANY PURPOSE DETRIMENT<br>INC. IT MAY NOT BE REPRODUC<br>IN ANY FORM WITHOUT THE W | TAL TO CUSTOM CA<br>CED OR TRANSCRIB | BLE<br>ED         | SMA-ST-PL/BNC-ST-JK G316 24I |                       | TOLERANCE:<br>0-18 inches +/- 1/2"<br>over 18" +/- 2% |  |
|   |                   |                  |  |                                      |                   | Part No:                     |                       | ASSEMBLY:<br>CENTER LABEL IF LENGT                    |  |
| CONTROLLED DOCUMENT - DO NOT COPY                   |                   |                  | ESTABLISHES AND AGREEMENT OF THE FOREGOING.  |                                      |                   |                              |                       | IS LESS THAN 12 INCHES                                |  |



## **RoHS 2015/863 Compliance Statement**

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 9/30/2023

Part Number: Q-3B0040005024I

Manufacturer: Amphenol Custom Cable

Description: SMA-ST-PL/BNC-ST-JK G316 24I

This information is valid as of the date indicated for the item (part number) listed.

**Director of Quality Assurance** 

Janice Frank