

Material and Finish

Shell: Steel, nickel plated
 Insulator: PBT thermoplastic with glass-fiber reinforcement, UL94V-0 rated
 Color: Black

Contact Material:
 Plug - Brass

- Contact Plating Options:
- Standard: gold flash on mating end, tin on termination end, nickel underplate on entire contact
 - 15 Option: 15u" gold on mating end, tin on termination end, nickel underplate on entire contact
 - 30 Option: 30u" gold on mating end, tin on termination end, nickel underplate on entire contact

Electrical Specifications

Rated Current: 1.5A
 Rated Voltage: 30Vac
 Insulation Resistance: more than 1000 megohms at 500V DC
 Contact Resistance: 13 milliohms max.
 Dielectric Withstanding Voltage: 1000V for 1 minute
 Operating Temperature: -55°C to +105°C

Ordering Information	
Part Number	Contact Area Plating Finish
KF86X-ED-15P-KJ	Gold Flash (standard option)
KF86X-ED-15P-KJ15	15u" Gold (15 option)
KF86X-ED-15P-KJ30	30u" Gold (30 option)

Ferrite Specifications	
Measured Value(OHM)	Test Frequency
12 MIN.	25 MHz.
30 MIN.	100 MHz.




Tolerances
X.X ± 0.30
X.XX ± 0.20
Unless Stated
Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	03/30/09	New Drawing	S. Vien	H. MA	S. Vien	01/13/09
A2	10/16/14	ECO#14-028	H. MA	P. DalCanto		
A3	05/10/16	ECO#16-009	H. MA	W. Cook		
A4	12/31/17	ECO #17-033	J. Elbanna	C. Furumasu		

KF86X-ED-15P-KJ

Vertical D-Sub, High Density, RoHS Compliant

JS, 15 Pin Male, Ferrite, K-Option



UNITS
mm