

Surge protection base element - VAL-MS BE-AR - 2801065

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Base element for Type 1 and Type 2 surge arresters of the VAL-MS series, with separate field and house termination, tool-free isolation disconnect, and test point. Design: 1-channel, bridgeable.



Product Features

- Versions with and without floating remote indication contact
- Separate field and house wire termination.
- Tool-free field wire disconnect and test point.
- IP20 touch safe when connected.
- Coding when protective plug is inserted for the first time
- Tested for railway applications



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	148.0 GRM
Custom tariff number	85363010
Country of origin	United States

Technical data

Dimensions

Height	153 mm
Width	17.7 mm
Depth	75 mm

Ambient conditions

Degree of protection	IP20
	IP20 (when disconnect closed)
Ambient temperature (operation)	-40 °C ... 80 °C
Altitude	max. 3000 m

Surge protection base element - VAL-MS BE-AR - 2801065

Technical data

Ambient conditions

Permissible humidity (operation)	5 % ... 95 %
Permissible humidity (storage/transport)	5 % ... 95 %
Shock (operation)	10g
Vibration (operation)	2g (0 ... 200 Hz)

General

Housing material	PA
Inflammability class according to UL 94	V0
Color	black
Total surge current (8/20) μ s	100 kA
Total surge current (10/350) μ s	15 kA
Mounting type	DIN rail mounting with additional retaining screw
Type	DIN rail module, two-section, divisible
Number of positions	1

Protective circuit

Nominal voltage U_N	500 V AC
Nominal frequency f_N	50 Hz (60 Hz)
Rated load current I_L	55 A (with 6 AWG)
Recommended backup fuse maximum	125 A (gL / gG)
Short-circuit resistance I_P with max. backup fuse (effective)	25 kA

Connection, protective circuit

Connection type IN	Screw terminal blocks
Connection type OUT	Screw terminal blocks
Screw thread	M5
Tightening torque	4.5 Nm
Stripping length	16 mm
Conductor cross section stranded min.	1.5 mm ²
Conductor cross section stranded max.	25 mm ²
Conductor cross section solid min.	1.5 mm ²
Conductor cross section solid max.	35 mm ²
Conductor cross section AWG/kcmil min.	15
Conductor cross section AWG/kcmil max	2
AWG conductor cross section	10 ... 2 (UL)

NEMA / UL data

Maximum Surge Current per Phase	100 kA
---------------------------------	--------

Surge protection base element - VAL-MS BE-AR - 2801065

Classifications

eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130802
eCl@ss 7.0	27130802
eCl@ss 8.0	27130802

ETIM

ETIM 3.0	EC000941
ETIM 4.0	EC001675
ETIM 5.0	EC001675

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

Drawings

Circuit diagram



Dimensioned drawing

