
32.768 kHz Tuning Fork

Features

- ± 20 ppm Initial Accuracy
- -20°C to $+70^{\circ}\text{C}$ or -40°C to $+85^{\circ}\text{C}$ Operating Temperature Range
- Small, Industry Standard Packages
- Products are Compliant to RoHS Directive and Fully Compatible with Lead-Free Assembly


Applications

- Realtime Clocks
- Microprocessors
- Wearables
- IoT
- Bluetooth Low Energy
- Medical, Hearing Aids, Meters and Monitors
- Security

General Description

The VMK series 32.768 kHz tuning fork is used as a building block for 32.768 kHz oscillator clocks, and associated divide-by to generate a 1 Hz/1 second clock signal. The VMK3 is a 3.2 mm x 1.5 mm ceramic hermetically sealed package and the VMK4 is 2.0 mm x 1.2 mm.

Block Diagram



1.0 ELECTRICAL CHARACTERISTICS

VMK3 ELECTRICAL PERFORMANCE

Parameter	Symbol	Min.	Typ.	Max.	Units
Nominal Frequency	f_{NOM}	—	32.768	—	kHz
Crystal Mode	—	Tuning Fork			—
Operating Temperature Range, <i>ordering option</i>	T_{OP}	-20	—	+70	°C
		-40	—	+85	
Frequency Stability					
Stability over T_{OP}	f_{STAB}	—	—	-0.04	ppm/°C ²
Turnover Temperature	—	20	25	30	°C
Frequency Tolerance, referenced to +25°C	f_{TOL}	—	—	±20	ppm
Load Capacitance, <i>ordering option</i>	C_{L}	6, 7, 9, or 12.5			pF
Equivalent Series Resistance	ESR	—	—	70	kΩ
Shunt Capacitance	C_{O}	—	1.2	3.0	pF
Motional Capacitance	C_{1}	—	3.5	—	fF
Drive Level	—	—	—	1.0	μW
Aging, 1st Year	f_{AGE}	—	—	±3	ppm
Storage Temperature	T_{STO}	-55	—	+125	°C
Package	—	3.2 x 1.5			mm
Weight	—	—	13	—	mg

Note 1: Product is compliant with RoHS directive and fully compatible with lead-free assembly.

VMK4 ELECTRICAL PERFORMANCE

Parameter	Symbol	Min.	Typ.	Max.	Units
Nominal Frequency	f_{NOM}	—	32.768	—	kHz
Crystal Mode	—	Tuning Fork			—
Operating Temperature Range, <i>ordering option</i>	T_{OP}	-20	—	+70	°C
		-40	—	+85	
Frequency Stability					
Stability over T_{OP}	f_{STAB}	—	—	-0.045	ppm/°C ²
Turnover Temperature	—	20	25	30	°C
Frequency Tolerance, referenced to +25°C	f_{TOL}	—	—	±20	ppm
Load Capacitance, <i>ordering option</i>	C_{L}	6, 7, 9, or 12.5			pF
Equivalent Series Resistance	ESR	—	—	90	kΩ
Shunt Capacitance	C_{O}	—	—	1.5	pF
Motional Capacitance	C_{1}	—	4.7	—	fF
Drive Level	—	—	—	1.0	μW
Aging, 1st Year	f_{AGE}	—	—	±3	ppm
Storage Temperature	T_{STO}	-55	—	+125	°C
Package	—	2.0 x 1.2			mm
Weight	—	—	6	—	mg

Note 1: Product is compliant with RoHS directive and fully compatible with lead-free assembly.

2.0 RELIABILITY AND IR COMPLIANCE

TABLE 2-1: ENVIRONMENTAL COMPLIANCE

Parameter	Conditions
Mechanical Shock	MIL-STD-883, Method 2002, Condition A
Mechanical Vibration	MIL-STD-883, Method 2007, Condition A
Temperature Cycle	MIL-STD-883, Method 1010, Condition B
Solderability	MIL-STD-202-210, Condition B
Gross and Fine Leak	MIL-STD-883, Method 1014
Altitude	MIL-STD-883, Method 1001, Condition B
Moisture Sensitivity Level	MSL 1




FIGURE 2-1: Solder Reflow Profile.

TABLE 2-2: REFLOW PROFILE

Parameter	Symbol	Value
Pre-Heat Time	t_S	60 sec. min.; 260 sec. max.
T_S min.	—	+150°C
T_S max.	—	+200°C
Ramp Up	R_{UP}	3°C/sec. max.
Time Above 217°C	t_L	60 sec. min.; 150 sec. max.
Time to Peak Temperature	t_{AMB-P}	480 sec. max.
Time at 260°C	t_P	10 sec. max.
Ramp Down	R_{DN}	6°C/sec. max.

Tuning fork products oscillate at frequency bands that are close to ultrasonic cleaning processes. This may cause electrical resonance deterioration and even damaging the overall structure of devices. Using ultrasonic cleaning machine to clean tuning fork devices should be avoided. If the use of this method to clean tuning fork devices is required, it's recommended to qualify the process and functionality of devices before and after the cleaning process.

3.0 TAPE AND REEL

TABLE 3-1: TAPE AND REEL DIMENSIONS

Tape Dimensions (mm)						Reel Dimensions (mm)							
Part #	W	F	Do	Po	P1	A	B	C	D	N	W1	W2	# per Reel
VMK3	12	5.5	1.5	4.0	4.0	180	2	13	21	60	13.0	15.4	3000
VMK4	8	3.5	1.5	4.0	4.0	178	2.5	13	21	60	9	11.4	3000




FIGURE 3-1: Tape and Reel Diagram.

4.0 PACKAGING INFORMATION

4.1 Package Marking Information

2-Lead VDFN*

XXXXYWW

Example

327021

2-Lead CDFP*

XXXXYWW

Example


327935

Legend: 327 32.768 kHz
 Y Year code (last digit of calendar year)
 WW Week code (week of January 1 is week '01')
 (e3) Pb-free JEDEC® designator for Matte Tin (Sn)
 * This package is Pb-free. The Pb-free JEDEC designator ((e3)) can be found on the outer packaging for this package.
 •, ▲, ▼ Pin one index is identified by a dot, delta up, or delta down (triangle mark).

Note: In the event the full Microchip part number cannot be marked on one line, it will be carried over to the next line, thus limiting the number of available characters for customer-specific information. Package may or may not include the corporate logo.
 Underbar (_) and/or Overbar (¯) symbol may not be to scale.


2-Lead VDFN 3.2 mm x 1.5 mm Package Outline and Recommended Land Pattern

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



2-Lead CDFP Package Outline and Recommended Land Pattern

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



APPENDIX A: REVISION HISTORY

Revision A (January 2021)

- Initial release of VMK3/VMK4 as Microchip data sheet DS20006440A.

PRODUCT IDENTIFICATION SYSTEM

To order or obtain information, e.g., on pricing or delivery, contact your local Microchip representative or sales office.

<u>Part No.</u>	<u>X</u>	<u>-X</u>	<u>X</u>	<u>X</u>	<u>-XX</u>	<u>XXXXXXXXXX</u>	<u>XX</u>
Device	Package	Mode	Frequency Tolerance	Operating Temperature	Load Capacitance	Frequency (in kHz)	Media Type
Device:	VMK:	32.768 kHz Tuning Fork					
Package:	3	=	2-Lead 3.2 mm x 1.5 mm VDFN				
	4	=	2-Lead 2.0 mm x 1.2 mm CDFP				
Mode:	1	=	Fundamental Tuning Fork				
Frequency Tolerance:	E	=	±20 ppm				
Operating Temperature:	E	=	-40°C to +85°C				
	J	=	-20°C to +70°C				
Load Capacitance:	06	=	6 pF				
	07	=	7 pF				
	09	=	9 pF				
	12	=	12.5 pF				
Frequency:	32K7680000	=	Frequency in kHz				
Packing Option:	<blank>	=	Cut Tape/non-TR Quantities				
	TR	=	3,000/Reel				
Examples:							
a) VMK3-1EE-06-32K7680000TR: 32.768 kHz Tuning Fork, 3.2 mm x 1.5 mm VDFN, Fundamental Tuning Fork, ±20 ppm Frequency Tolerance, -40°C to +85°C Temp. Range, 6 pF Load Capacitance, 3,000/Reel							
b) VMK4-1EJ-12-32K7680000TR: 32.768 kHz Tuning Fork, 2.0 mm x 1.2 mm CDFP, Fundamental Tuning Fork, ±20 ppm Frequency Tolerance, -20°C to +70°C Temp. Range, 12.5 pF Load Capacitance, 3,000/Reel							
Note 1: Tape and Reel identifier only appears in the catalog part number description. This identifier is used for ordering purposes and is not printed on the device package. Check with your Microchip Sales Office for package availability with the Tape and Reel option.							

Note the following details of the code protection feature on Microchip devices:

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is secure when used in the intended manner and under normal conditions.
- There are dishonest and possibly illegal methods being used in attempts to breach the code protection features of the Microchip devices. We believe that these methods require using the Microchip products in a manner outside the operating specifications contained in Microchip's Data Sheets. Attempts to breach these code protection features, most likely, cannot be accomplished without violating Microchip's intellectual property rights.
- Microchip is willing to work with any customer who is concerned about the integrity of its code.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not mean that we are guaranteeing the product is "unbreakable." Code protection is constantly evolving. We at Microchip are committed to continuously improving the code protection features of our products. Attempts to break Microchip's code protection feature may be a violation of the Digital Millennium Copyright Act. If such acts allow unauthorized access to your software or other copyrighted work, you may have a right to sue for relief under that Act.

Information contained in this publication is provided for the sole purpose of designing with and using Microchip products. Information regarding device applications and the like is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications.

THIS INFORMATION IS PROVIDED BY MICROCHIP "AS IS". MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL OR CONSEQUENTIAL LOSS, DAMAGE, COST OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP'S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION. Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

Trademarks

The Microchip name and logo, the Microchip logo, Adaptec, AnyRate, AVR, AVR logo, AVR Freaks, BesTime, BitCloud, chipKIT, chipKIT logo, CryptoMemory, CryptoRF, dsPIC, FlashFlex, flexPWR, HELDO, IGL00, JukeBlox, KeeLoq, Kleer, LANCheck, LinkMD, maXStylus, maXTouch, MediaLB, megaAVR, Microsemi, Microsemi logo, MOST, MOST logo, MPLAB, OptoLyzer, PackeTime, PIC, picoPower, PICSTART, PIC32 logo, PolarFire, Prochip Designer, QTouch, SAM-BA, SenGenuity, SpyNIC, SST, SST Logo, SuperFlash, Symmetricom, SyncServer, Tachyon, TimeSource, tinyAVR, UNI/O, Vectron, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

AgileSwitch, APT, ClockWorks, The Embedded Control Solutions Company, EtherSynch, FlashTec, Hyper Speed Control, HyperLight Load, IntelliMOS, Libero, motorBench, mTouch, Powermite 3, Precision Edge, ProASIC, ProASIC Plus, ProASIC Plus logo, Quiet-Wire, SmartFusion, SyncWorld, Temux, TimeCesium, TimeHub, TimePictra, TimeProvider, WinPath, and ZL are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, Augmented Switching, BlueSky, BodyCom, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, Espresso T1S, EtherGREEN, IdealBridge, In-Circuit Serial Programming, ICSP, INICnet, Intelligent Paralleling, Inter-Chip Connectivity, JitterBlocker, maxCrypto, maxView, memBrain, Mindi, MiWi, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, Omniscient Code Generation, PICDEM, PICDEM.net, PICkit, PICtail, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, RTAX, RTG4, SAM-ICE, Serial Quad I/O, simpleMAP, SimpliPHY, SmartBuffer, SMART-I.S., storClad, SQI, SuperSwitcher, SuperSwitcher II, Switchtec, SynchroPHY, Total Endurance, TSHARC, USBCheck, VariSense, VectorBlox, VeriPHY, ViewSpan, WiperLock, XpressConnect, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

The Adaptec logo, Frequency on Demand, Silicon Storage Technology, and Symmcom are registered trademarks of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2021, Microchip Technology Incorporated, All Rights Reserved.

ISBN: 978-1-5224-7500-2

For information regarding Microchip's Quality Management Systems, please visit www.microchip.com/quality.



MICROCHIP

Worldwide Sales and Service

AMERICAS

Corporate Office
2355 West Chandler Blvd.
Chandler, AZ 85224-6199
Tel: 480-792-7200
Fax: 480-792-7277
Technical Support:
<http://www.microchip.com/support>
Web Address:
www.microchip.com

Atlanta

Duluth, GA
Tel: 678-957-9614
Fax: 678-957-1455

Austin, TX

Tel: 512-257-3370

Boston

Westborough, MA
Tel: 774-760-0087
Fax: 774-760-0088

Chicago

Itasca, IL
Tel: 630-285-0071
Fax: 630-285-0075

Dallas

Addison, TX
Tel: 972-818-7423
Fax: 972-818-2924

Detroit

Novi, MI
Tel: 248-848-4000

Houston, TX

Tel: 281-894-5983

Indianapolis

Noblesville, IN
Tel: 317-773-8323
Fax: 317-773-5453
Tel: 317-536-2380

Los Angeles

Mission Viejo, CA
Tel: 949-462-9523
Fax: 949-462-9608
Tel: 951-273-7800

Raleigh, NC

Tel: 919-844-7510

New York, NY

Tel: 631-435-6000

San Jose, CA

Tel: 408-735-9110
Tel: 408-436-4270

Canada - Toronto

Tel: 905-695-1980
Fax: 905-695-2078

ASIA/PACIFIC

Australia - Sydney
Tel: 61-2-9868-6733

China - Beijing
Tel: 86-10-8569-7000

China - Chengdu
Tel: 86-28-8665-5511

China - Chongqing
Tel: 86-23-8980-9588

China - Dongguan
Tel: 86-769-8702-9880

China - Guangzhou
Tel: 86-20-8755-8029

China - Hangzhou
Tel: 86-571-8792-8115

China - Hong Kong SAR
Tel: 852-2943-5100

China - Nanjing
Tel: 86-25-8473-2460

China - Qingdao
Tel: 86-532-8502-7355

China - Shanghai
Tel: 86-21-3326-8000

China - Shenyang
Tel: 86-24-2334-2829

China - Shenzhen
Tel: 86-755-8864-2200

China - Suzhou
Tel: 86-186-6233-1526

China - Wuhan
Tel: 86-27-5980-5300

China - Xian
Tel: 86-29-8833-7252

China - Xiamen
Tel: 86-592-2388138

China - Zhuhai
Tel: 86-756-3210040

ASIA/PACIFIC

India - Bangalore
Tel: 91-80-3090-4444

India - New Delhi
Tel: 91-11-4160-8631

India - Pune
Tel: 91-20-4121-0141

Japan - Osaka
Tel: 81-6-6152-7160

Japan - Tokyo
Tel: 81-3-6880-3770

Korea - Daegu
Tel: 82-53-744-4301

Korea - Seoul
Tel: 82-2-554-7200

Malaysia - Kuala Lumpur
Tel: 60-3-7651-7906

Malaysia - Penang
Tel: 60-4-227-8870

Philippines - Manila
Tel: 63-2-634-9065

Singapore
Tel: 65-6334-8870

Taiwan - Hsin Chu
Tel: 886-3-577-8366

Taiwan - Kaohsiung
Tel: 886-7-213-7830

Taiwan - Taipei
Tel: 886-2-2508-8600

Thailand - Bangkok
Tel: 66-2-694-1351

Vietnam - Ho Chi Minh
Tel: 84-28-5448-2100

EUROPE

Austria - Wels
Tel: 43-7242-2244-39
Fax: 43-7242-2244-393

Denmark - Copenhagen
Tel: 45-4485-5910
Fax: 45-4485-2829

Finland - Espoo
Tel: 358-9-4520-820

France - Paris
Tel: 33-1-69-53-63-20
Fax: 33-1-69-30-90-79

Germany - Garching
Tel: 49-8931-9700

Germany - Haan
Tel: 49-2129-3766400

Germany - Heilbronn
Tel: 49-7131-72400

Germany - Karlsruhe
Tel: 49-721-625370

Germany - Munich
Tel: 49-89-627-144-0
Fax: 49-89-627-144-44

Germany - Rosenheim
Tel: 49-8031-354-560

Israel - Ra'anana
Tel: 972-9-744-7705

Italy - Milan
Tel: 39-0331-742611
Fax: 39-0331-466781

Italy - Padova
Tel: 39-049-7625286

Netherlands - Drunen
Tel: 31-416-690399
Fax: 31-416-690340

Norway - Trondheim
Tel: 47-7288-4388

Poland - Warsaw
Tel: 48-22-3325737

Romania - Bucharest
Tel: 40-21-407-87-50

Spain - Madrid
Tel: 34-91-708-08-90
Fax: 34-91-708-08-91

Sweden - Gothenberg
Tel: 46-31-704-60-40

Sweden - Stockholm
Tel: 46-8-5090-4654

UK - Wokingham
Tel: 44-118-921-5800
Fax: 44-118-921-5820