


- Note 1. The floating portion of U.FLP-ML51-J-PA(F)-ST shall not be used in  
 wrenched conditions nor to be inserted at an angle.
2. Avoid using thick cables or stiff cables which will  
 interfere with the floating function.  
 The cable connection shall be connected properly not  
 to stress and wrench the floating portion.
3. All the dimensions and conditions are guaranteed only when mated to  
 U.FL-R-SMT-1(\*\*) manufactured by Hirose Electric Co., Ltd.



[FLOATING POSITION]

HRS DRAWING FOR REFERENCE

ROHS COMPLIANT

NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
7	BRASS	NICKEL PLATING	14	STAINLESS STEEL	GOLD PLATING
6	BRASS	NICKEL PLATING	13	PTFE	
5	STAINLESS STEEL	GOLD PLATING	12	BERYLLIUM COPPER	GOLD PLATING
4	PTFE		11	BRASS	GOLD PLATING
3	BERYLLIUM COPPER	GOLD PLATING	10	PTFE	
2	PTFE		9	PHOSPHOR BRONZE	NICKEL PLATING
1	BRASS	NICKEL PLATING	8	STAINLESS STEEL	

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1					

APPROVED : MH. YAMANE	09.09.29	DRAWING NO.	EDC3-327068-00
CHECKED : MH. YAMANE	09.09.29	PART NO.	U.FLP-ML51-J-PA(F)-ST
DESIGNED : NK. NINOMIYA	09.09.25	CODE NO.	CL311-0446-8-00
DRAWN : NK. NINOMIYA	09.09.25		

**HRS**

HIROSE  
ELECTRIC  
CO., LTD.