

## Specification Sheet

Part Number: 156-00455

PEEK material provides excellent resistance to extreme temperature environments.

Two piece assembly allows the mount to slide along the strap ensuring proper orientation.

Arrowhead style mount provides low insertion and high extraction force.

Arrowhead disc protects against dirt and other impurities.



2-Piece Cable Tie/Arrowhead Mount, 7.9"L,50lb, 0.25 - 0.26" Mounting Hole, PA46/PEEK, Gray/Bge, 100/pkg

Article Number

156-00455

Type

T50ROSP1SFT6.5

Color

Beige (BGE) Gray (GY)

Quantity Per

bag

Product Description

The Arrowhead Mount Tie is a two-piece bundling and fastening solution that delivers strong extraction force. The disc blocks debris ingress through the mounting hole. This convenient combination is used in many markets, including automobile, aircraft and appliance.

Short Description

2-Piece Cable Tie/Arrowhead Mount, 7.9"L,50lb, 0.25 - 0.26" Mounting Hole, PA46/PEEK, Gray/Bge, 100/pkg

Global Part Name

T50ROSP1SFT6.5-PA46/PEEK-GY/BGE

Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225.0
Length L (Imperial)	7.9
Length L (Metric)	200.0
Fixation Method	Arrowhead
Identification Plate Position	none
Tie Closure	plastic pawl
Variant	Outside Serrated
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.04
Bundle Diameter Min (Metric)	1.0
Bundle Diameter Max (Imperial)	1.8
Bundle Diameter Max (Metric)	45.0
Thickness T (Imperial)	0.05
Thickness T (Metric)	1.3

Height H (Imperial) 0.59

Height H (Metric) 15.0

Panel Thickness Min (Imperial) 0.03

Panel Thickness Max (Imperial) 0.05

Panel Thickness Min (Metric) 0.7

Panel Thickness Max (Metric) 1.3

Mounting Hole Diameter D (Imperial) 0.25 - 0.26

Mounting Hole Diameter D (Metric) 6.3 - 6.7 mm

Mounting Hole Diameter D Min (Imperial) 0.25

Mounting Hole Diameter D Max (Imperial) 0.26

Mounting Hole Diameter D Max (Metric) 6.7

Disc Diameter (Metric) 16.0

Disc Diameter (Imperial) 0.63

Material Polyamide 4.6 (PA46) Polyetheretherketone (PEEK)

Material Shortcut PEEK PA46

Material Cable Tie	Polyamide 4.6 (PA46)
Flammability	UL 94 V-2
Operating Temperature	-40°F to +266°F (-40°C to +130°C) -67°F to +464°F (-55°C to +240°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Disclaimer](#)   [Terms and Conditions](#)