36 INCHES LENGTH



Connector A 132245 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B FA1-NZSJ-C01-0 FAKRA Jack Straight Brass Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

	Connector A		Cable			Connector B		
De Ty Ge Bo Co Po Im Mo Bo Bo IP Co Co Ma	art #: 132245 escription: 5000 ype: SMA R/A BH 5000 ype: SMA ender: Jack ody Type: Right Angle ontact Type: Solder oblarity: Standard npedance: 50 Ohm ounting: Bulkhead - R body Material: Brass ody Finish: Gold Rating: None ontact Material: Beryllium Cop ontact Finish: Gold ax. Freq.: 12.4 GHz ooting: SMA Jack Rig	pper	Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 36 Inches	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	FA1-NZSJ-C01-0 FAKRA-Z JK RG174 FAKRA Jack Straight Crimp Standard 50 Ohm Cable Brass Nickel None Beryllium Copper Gold 3 GHz FAKRA-Z Jack Strai 0°		
Amphenol CUSTOM CABLE CONTROLLED DOCUMENT - DO NOT COPY THIS DRAWING MAY CONTAI PROPRIETARY INFORMATION FOR ANY PURPOSE DETRIMENT INC. IT MAY NOT BE REPROD IN ANY FORM WITHOUT THE CUSTOM CABLE INC. ACCEPT ESTABLISHES AND AGREEME		AND MUST NOT BE USED TAL TO CUSTOM CABLE CED OR TRANSCRIBED RITTEN CONSENT OF NCE OF THIS DRAWING Part No:		AZ-ST-JK G174 36I		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES		