



SPECIFICATIONS:

TIP ROD, RING & SLEEVE - BRASS, NICKEL PLATED

SCREWS - BRASS

TERMINALS - BRASS, HOT TINNED

INSULATION - POLYESTER, GLASS FILLED UL94V-0

CUSTOMER DRAWING

CAD/CAM DWG. NO.

483N\_CD

SHEET 1 OF 1

★ STAR SYMBOL DENOTES CRITICAL DIMENSION. SEE S/C ENGINEERING STANDARD ES-0001

THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSE ONLY.

UNLESS OTHERWISE SPECIFIED

SIZE	WIDTH	MULT	LBS./M	TEMPER
------	-------	------	--------	--------

1. ALL DIMENSIONS IN INCHES
2. DECIMAL DIMENSIONS ±.005
3. FRACTIONAL DIMENSIONS ±1/64
4. ANGLES ±1/2°
5. ALL DIA'S CONCENTRIC WITHIN .005 T.I.R.
6. REMOVE ALL BURRS
7. MAKE NO DIMENSIONAL ALLOWANCES FOR APPLIED FINISHES, I.E., PLATING, PAINTING, ETC.
8. HOLES ON THE SAME CENTERLINE MUST BE ALIGNED WITHIN ±.002

FINISH	MATERIAL
SPEC. NO.	SPEC. NO.

FIRST USED ON	SCALE
	1:0.50

DATE DRAWN	BY	CHK'D	APP'D
7-21-93	ES	TAO 7-27-93	GHJ 7-26-93

**Switchcraft®**

B	ECO #20627	1-23-96	DEA	TAO
A	FIRST DRAWN	7-21-93	ES	GHJ
ISSUE	CHANGE NO.	DATE	BY	APP'D

NAME	PART NO.	ISSUE
LITTEL PLUG	483N	B

REVISIONS

DO NOT SCALE DRAWING

