



CORE DIMENSIONS		28T0155-000			
UNCOATED CORE					
		MM	INCHES	MM	INCHES
OD	3.94	(.155)	±	.13	(.005)
ID	2.24	(.088)	±	.13	(.005)
TH	2.54	(.100)	±	.13	(.005)
SINGLE PARYLENE COATING		28T0155-00P			
OD	3.96	(.156)	±	.15	(.006)
ID	2.21	(.087)	±	.15	(.006)
TH	2.57	(.101)	±	.15	(.006)

WEIGHT / K 0.23 LBS
 INITIAL PERMEABILITY 850

ELECTRICAL SPECIFICATION								
	MIN		NOM	MAX	MAX	FREQ.	VOLT.	
	(μH)	MIN TOL.	(μH)	(μH)	TOL.	(kHz)	(mV)	TURNS
L	.183	(-25%)	.244	.305	(+25%)	100	100	1
Q	REF	-	-	-	-	100	100	1
Net	MIN		NOM			FREQ.		
Impedance	(Ω)	TOL	(Ω)			(MHz)		TURNS
Z1 (Ref.)	7.72	(-25%)	10.30	-	-	25	-	1
Z2	14.59	(-25%)	19.45	-	-	150	-	1

COATING SPECIFICATIONS			
	TYPE	Max. Coating (mils.)	Min. DLB VAC TEST FORCE (LB)
	PARYLENE	0.5	1000 0.13

NOTES:

1. Material and coating should be Halogen Free. (Br+Cl < 900ppm)
2. Lairdtech ferrite material 28#.
3. Coating material: Parylene N
4. R=0.10~0.40mm around inner and outer edges.
5. Operating temperature: -40 to +85 °C.



Rev	Description	Date	INT
A	Original Draft	1995/6/30	JBE
B	UPDATED TO NEW FORMAT	1995/6/30	JBE
C	UPDATED ELECT & Z SPECS	1996/5/6	BAC
D	TRANSFER TO LOTUS NOTES	1997/11/12	IS
E	REVISED GAUSS TO 10	2003/12/17	TPM
F	REM Q SPECS CHANGE PART NUMBER	2005/9/30	JRK
G	Revised Template	2006/6/1	WMM
H	Add Notes, updated L spec and DIM	2009/6/12	Jcai

Date: 6/12/2009	DWG # 28T0155-00P-H	Rev:
Drawn By: Jcai	Title # 28T0155-00P	H

Steward This document contains information which is proprietary to Steward. No production or publication of this document in whole or in part shall be made without written authorization from Steward.

UNCONTROLLED DOCUMENT