

EPC 1522 - Edge device



1185423

<https://www.phoenixcontact.com/us/products/1185423>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



PLCnext Industrial Edge Computer with Intel® Celeron® N3350 processor. This small form factor programmable edge device supports IEC 61131-3, MATLAB Simulink, C/C++, and is perfect for protocol converting, data collection, and cloud computing.

Your advantages

- Local output of visualizations via DisplayPort
- Seamless support in PLCnext Engineer for OT programming
- Connection to PROFICLOUD
- Connection to PLCnext Store, for installing e.g. Node-RED, InfluxDB or Docker-Portainer
- Numerous protocols supported such as: http, https, FTP, SNTP, SNMP, SMTP, SQL, MySQL, DCP, etc.
- Two independent Ethernet interfaces and WIFI
- High-level programming languages: IEC61131-3, C/C++, MATLAB Simulink
- Consistent graphical programming interfaces

Commercial data

Item number	1185423
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DR12
Product key	DRBABE
GTIN	4063151225568
Weight per piece (including packing)	952 g
Weight per piece (excluding packing)	730 g
Customs tariff number	84715000
Country of origin	TW

EPC 1522 - Edge device



1185423

<https://www.phoenixcontact.com/us/products/1185423>

Technical data

Product properties

Type	Stand-Alone
Product type	Controller
Product family	PLCnext Control

Computer data

Processor	Intel® Celeron® N3350 1.10/2.4 GHz
Cooling	passive
RAM	4 GB LPDDR4
Data storage system	128 GB M.2 SSD

Display

Display type	none
--------------	------

System properties

Retentive data storage	Remanent data is not supported
------------------------	--------------------------------

IEC 61131 runtime system

Program memory	8 Mbyte
Data storage system	12 Mbyte

Functionality

Programming languages supported	Instruction list (IL)
	Symbolic flowchart (SFC)
	Ladder diagram (LD)
	Function block diagram (FBD)
	Structured text (ST)
	C++
	C#
	Java
	Python
	Simulink

System requirements

Engineering tool	PLCnext Engineer
	Eclipse
	Visual Studio
	MATLAB® Simulink®

Electrical properties

Supply

Supply voltage	24 V DC
----------------	---------

EPC 1522 - Edge device



1185423

<https://www.phoenixcontact.com/us/products/1185423>

Interfaces

Interfaces	1x DP++
	2x USB 3.0
	2x COM ports
	1x Wireless LAN
LAN chipset	Intel® I210-AT

Dimensions

External dimensions

Width / Height / Depth	99 mm / 92 mm / 63 mm
------------------------	-----------------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP30
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	5 % ... 85 % (non-condensing)
Shock	15g, 11 ms in accordance with IEC 60068-2-27
Vibration (operation)	1g, according to EN 60068-2-6

Approvals

Conformity/Approvals

Conformance	CE-compliant
FCC	Title 47 Part 15 Subpart B:2018 Class A

Mounting

Mounting type	DIN rail mounting
	Wall mounting

EPC 1522 - Edge device



1185423

<https://www.phoenixcontact.com/us/products/1185423>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1185423>



IECEE CB Scheme

Approval ID: US-39601-UL



EAC

Approval ID: RU C-DE.A*08.B01708



UL Listed

Approval ID: FILE E 238705



cUL Listed

Approval ID: FILE E 238705



EAC-RoHS

Approval ID: RU*-DE*HB.B.00386/20

cULus Listed

EPC 1522 - Edge device

1185423

<https://www.phoenixcontact.com/us/products/1185423>



Classifications

ECLASS

ECLASS-11.0	19200102
ECLASS-12.0	19200102
ECLASS-13.0	19200102

ETIM

ETIM 8.0	EC001413
----------	----------

UNSPSC

UNSPSC 21.0	43211500
-------------	----------

EPC 1522 - Edge device

1185423

<https://www.phoenixcontact.com/us/products/1185423>



Environmental product compliance

REACH SVHC

Lead 7439-92-1

EPC 1522 - Edge device

1185423

<https://www.phoenixcontact.com/us/products/1185423>



Accessories

DP TO VGA ADPTR - Adapter

2400173

<https://www.phoenixcontact.com/us/products/2400173>

DisplayPort to VGA video adapter



DP TO DVI ADPTR - Adapter

2400174

<https://www.phoenixcontact.com/us/products/2400174>

DisplayPort to DVI-i video adapter



EPC 1522 - Edge device

1185423

<https://www.phoenixcontact.com/us/products/1185423>



VL 2.0M DP CABLE - Connecting cable

2404774

<https://www.phoenixcontact.com/us/products/2404774>

DisplayPort (DP) cable (2 m) for use with industrial computers



BL2 BPC 1500 WALL MOUNT KIT - Mounting kit

1147655

<https://www.phoenixcontact.com/us/products/1147655>

Mounting kit



EPC 1522 - Edge device

1185423

<https://www.phoenixcontact.com/us/products/1185423>



BL2 BPC 1500 DIN RAIL KIT - Mounting kit

1147464

<https://www.phoenixcontact.com/us/products/1147464>



DIN rail mounting kit for BL2 BPC 15... products

MC 1,5/ 2-STF-3,5 - PCB connector

1847055

<https://www.phoenixcontact.com/us/products/1847055>



PCB connector, nominal cross section: 1.5 mm², color: green, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Tin, contact connection type: Socket, number of potentials: 2, number of rows: 1, number of positions: 2, number of connections: 2, product range: MC 1,5/...-STF, pitch: 3.5 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, plug-in system: COMBICON MC 1,5, locking: Screw locking mechanism, mounting: Screw flange, type of packaging: packed in cardboard

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com