



RESISTANCE VS TEMPERATURE CHARACTERISTICS:

Temp(°C)	R min (KΩ)	R nom (KΩ)	R max (KΩ)	Temp(°C)	R min (KΩ)	R nom (KΩ)	R max (KΩ)
-40	246.7	257.4	268.5	50	3.816	3.891	3.967
-35	182.8	190.1	197.8	55	3.202	3.270	3.340
-30	136.9	142.0	147.3	60	2.698	2.761	2.825
-25	103.6	107.1	110.8	65	2.284	2.341	2.399
-20	79.090	81.580	84.150	70	1.941	1.993	2.045
-15	60.950	62.700	64.500	75	1.656	1.703	1.751
-10	47.360	48.610	49.870	80	1.419	1.461	1.504
-5	37.100	37.980	38.870	85	1.221	1.259	1.298
0	29.280	29.900	30.530	90	1.054	1.088	1.124
5	23.250	23.680	24.130	95	0.913	0.944	0.977
10	18.590	18.900	19.210	100	0.794	0.822	0.851
15	14.970	15.190	15.400	105	0.692	0.718	0.745
20	12.140	12.280	12.430	110	0.606	0.629	0.653
25	9.900	10.000	10.100	115	0.531	0.552	0.574
30	8.092	8.190	8.288	120	0.467	0.487	0.507
35	6.652	6.746	6.840	125	0.412	0.430	0.448
40	5.499	5.587	5.676	130	0.357	0.373	0.389
45	4.569	4.651	4.734	135	0.302	0.316	0.330

NOTES:

1. RESISTANCE @ 25°C : 10KΩ±1%
2. BETA VALUE (0/50°C) : 3600K±1%
3. OPERATING TEMPERATURE RANGE : -40°C TO +135°C.
4. DISSIPATION FACTOR : 1.5mW/°C
5. THERMAL TIME CONSTANT : LESS THAN 3SECONDS IN WATER
- 6.INSULATION RESISTANCE : 10MΩ AT 100 VDC

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC:		molex					
	△/A = 0	mm NTS								
DIVISIONAL SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 657230 DRWN: RAVIKM 2021/03/04 CHK'D: RBBHASKAR 2021/03/05 APPR: RBBHASKAR 2021/03/05		PRODUCT CUSTOMER DRAWING					
	△/E = 0	ANGULAR TOL ± °								
DIVISIONAL SYMBOLS	4 PLACES	±	INITIAL REVISION: DRWN: RAVIKM 2021/03/04 APPR: RBBHASKAR 2021/03/05		DOCUMENT NUMBER		DOC TYPE	DOC PART	REVISION	
	3 PLACES	±			2152703603		PSD	000	A	
	2 PLACES	±			MATERIAL NUMBER		CUSTOMER		SHEET NUMBER	
	1 PLACE	±			A3-SIZE 215270		2152703603		OTS 1 OF 1	
	0 PLACES	±	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION					