

APPLICATOR PARTS LIST

TYPE

Splice - Lengthwise

AMP INCORPORATED
HARRISBURG, PENNA.

THIS IS A CONTROLLED DOCUMENT

| NO. | DESCRIPTION | REQ. | PART NO. | NO. | DESCRIPTION | REQ. | PART NO. |
|-----|----------------------------------|------|---------------------|---------------|----------------------------|------|---------------------|
| 1 | WIRE CRIMPER | 1 | 377586 | 42 | Guard End | 1 | 377586 |
| 2 | INS. CRIMPER | | | 43 | Spring Guide | 1 | 2-24017-7 |
| 3 | ANVIL | 1 | 374764 | 44 | Feed Plate Retainer | 1 | 372928 |
| 4 | ANVIL SPACER | | | 45 | | | |
| 5 | SHEAR BLADE | 1 | 472672 | 46 | | | |
| 6 | WEAR BLOCK PLATE-Feed | 1 | 386595 | 47 | | | |
| 7 | SHEAR BLADE SPACER | | | 48 | | | |
| 8 | FRONT SHEAR PLATE | | | 49 | | | |
| 9 | REAR ANVIL SPACER PLT. | | | 50 | | | |
| 10 | FRONT ANVIL SPACER PLT. | | | 51 | | | |
| 11 | TOOL SPACER | | | 52 | | | |
| 12 | CRIMP SPACER | | | 53 | | | |
| 13 | FRONT STRIP GUIDE | | | 54 | | | |
| 14 | REAR STRIP GUIDE | | | 55 | Sq. Hd. Set Scr. Depressor | 1 | 21077-8 |
| 15 | RAM | 1 | 471057 | 56 | Nut - Jam | 1 | 22202-1 |
| 16 | TOOL HOLDER | | | 57 | | | |
| 17 | ADJ. CRIMP MOUNT | | | 58 | | | |
| 18 | ADJ. BLOCK | | | 59 | | | |
| 19 | APPLICATOR MOUNT ASSY. | 1 | 473933 | 60 | | | |
| 20 | BASE PLATE | | | 61 | | | |
| 21 | BASE BLOCK | | | 62 | | | |
| 22 | STRIP GUIDE PLATE | | | 63 | | | |
| 23 | ANVIL HOLDER | 1 | 374348 | 64 | MECH FEED | 1 | 692140-2 |
| 24 | AUX. ANVIL HOLDER | 1 | 378975 | 65 | TENSION ADJ. PLATE | 1 | 374999 |
| 25 | STRIPPER WIRE GUIDE | 1 | 376945 | MISCELLANEOUS | | | |
| 26 | STRIPPER WIRE | 1 | 810995-2 | 66 | LUBRICATOR ASSY. | 1 | 465184-2 |
| 27 | STRIPPER SPACER STR. | 1 | 379011 | 67 | OIL, SYNTHETIC | REF | 852931-2 |
| 28 | STRIPPER MOUNT BRACKET | | | 68 | | | |
| 29 | STRIPPER BUSHING | | | 69 | | | |
| 30 | STOCK DRAG | 1 | 372990 | 70 | | | |
| 31 | STOCK DRAG HANDLE NUT | 1 | 21022-4 | 71 | | | |
| 32 | STOCK DRAG STUD | 1 | 21015-8 | 72 | | | |
| 33 | STOCK DRAG SPRING | 1 | 210578-1 | REV. | REVISION RECORD | DATE | BY |
| 34 | STOCK DRAG ADJ. SCREW | 2 | 372997 | S1 | ECR-06-002549 | 2-06 | ml/66 |
| 35 | FEED FINGER HOLDER | | | | | | |
| 36 | FEED FINGER | 1 | 370000 | | | | |
| 37 | FEED FINGER TIP | | | | | | |
| 38 | FEED FINGER SPACER | | | | | | |
| 39 | BASE CASTING | 1 | 570238 | | | | |
| 40 | GUARD | 1 | 473071 | | | | |
| 41 | Bracket Guard | 1 | 376946 | | | | |

| CRIMPING DATA | | | TERMINALS |
|------------------------------------|---|----------------|----------------|
| TO APPLY TERMINAL SPEC 114-2088 | | | 40866 41210 |
| WIRE SIZE | CRIMP HEIGHT | 40999 | |
| (2) 16 | .103 | 41627 60192 | |
| CRIMP WIRE | SIZE .155 | TYPE F | FEED .300 |
| INSUL. | | | |
| SLEEVED | | | |
| INSULATION RANGE | WIRE RANGE 4000-10,000 CMA | | |
| EXPLODED VIEW | A-6010-1 A-6010-2 | | |
| REMARKS: | THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION. | | |
| | <input checked="" type="checkbox"/> DENOTES WEARING PARTS <input type="checkbox"/> RECOMMEND PURCHASE REPLACEMENT | | |
| | THIS APPLICATOR IS TO BE USED ON | | |
| | AMP-O-LECTRIC 1-471273-3 MECH FEED | | |
| | AMP-O-LECTRIC MECH FEED 692140-2 | | |
| | | | 4 |
| SERIAL NO. | DATE SHIPPED | DESIGNED | |
| CUSTOMER NAME AND ADDRESS | | | CHK'D. 4/1/86 |
| | | | APP'D. |
| APPLICATOR NUMBER | REV. S1 | 671061-1 | SHEET OF |

2000
 RELEASED FOR REPLICATION
 BY AMP INCORPORATED ALL RIGHTS RESERVED
 COPYRIGHT 2000
 THIS DRAWING IS UNCLASSIFIED