



Material
 Contact Pin: Brass
 Insulator (housing): Thermoplastic (UL94V-0), Green
 Surface of solder tail: Tin plated

Electrical cULus / VDE
 Voltage rating: 300VAC / 300VAC
 Current rating: 8A / 10A
 Wire range:
 Solid wire(AWG):
 Wire strip length:
 Withstanding Voltage: 1.6KV / 2.5KV
 Operating temperature: -30°C to +105°C
 Soldering temperature: 250°C±10°C/5 Sec
 Safety Approval:

N= NUMBER OF CONTACTS

RoHS compliant

Unit:mm



File No.: E349947

| | | | | | | | | |
|-----------|-------|-----|--------------|------------|--------|----------|-------------|--|
| Scale | 1:1 | | | | | Date | Name | Customer-No. |
| TOLERANCE | | | | | | Drawn | 10.12.2009 | Dean |
| X. | ±0.50 | | | | | Approved | 01.04.2016 | Joanna |
| X.X | ±0.30 | | | | | | | |
| X.XX | ±0.10 | | | | | | | |
| DIM | TOL | ② | Add UL | 01.04.2016 | Joanna | | | Drawing-No. |
| X.° | ±1° | ① | Drawn | 10.12.2009 | Dean | | | ASSMANN WSW-No. A-TB381-VKxx |
| Angle | TOL | Id. | Modification | Date | Name | Replace | ASS 3840 CO | rev02 |
| | | | | | | | | Sheet |

1

2

3

4

5

6

7