



NOTES:

1. METALSHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
2. INSULATOR: HIGH TEMPERATURE PLASTIC UL 94 V-0, BLACK
3. CONTACTS: COPPER ALLOY
PLATING: 8µm HARD GOLD over min. 50µm NICKEL
SOLDER CUP ACCEPTS CABLE AWG 20
4. CAPACITANCE: 2 x 180pF ±20%
5. DIELECTRIC WITHSTANDING VOLTAGE: 300 VDC
6. MAXIMUM TORQUE VALUE FOR THREAD: 6 in.LB
7. CONNECTOR IS PART MARKED: 242A29140X CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND					tolerance		scale: 2:1 (5:1)
					dim. in mm		material: SEE NOTES
					date	name	title: D-SUB PI FILTER FEMALE
					drawn	20.03.09	Sonnenberg
					appd.	20.03.09	Fischer
					norm		9pos. SOLDER CUP with threaded insert
					d-old		dwg no: 24K1A1164
1 x b	Ä4234	26.03.12	K.H.	CONEC [®]			DIN-A3
a	Original						sh: 1
rev.	description	date	name	part no: 242A29140X			