



SECTION A-A

If this document is printed it becomes uncontrolled.
Check with the web for latest revision.

REVISIONS			
LTR	DESCRIPTION	DATE	APPROVED
B	REVISED PER ECN T-013038	9/24/83	[Signature]
C	Revised Per ECN T-20719	96/4/16	M. H. [Signature]

NOTES:

- THIS CTM IS DESIGNED TO MEET THE REQUIREMENTS OF RAYCHEM SPECIFICATION D-6116.
- MODULE BODY:
TRANSPARENT BLUE HEAT SHRINKABLE RADIATION CROSS LINKED PVF₂
- CONTACT STRIP:
COPPER ALLOY 172 PER QQ-C-533
SOLDER COATED PER QQ-S-571, Sn63
FLUX COATED PER QQ-S-571, TYPE RMA
- FLAT CABLE SEAL:
MODIFIED THERMOPLASTIC SEALANT
- USABLE CABLE SIZE:
FLAT CONDUCTOR CABLE: 28 GAUGE TU400528B
- CONSULT FACTORY FOR RAYCHEM ENGINEERING STANDARD FOR TERMINATION METHOD.
- DIELECTRIC WITHSTANDING VOLTAGE:

TEST CONDITION	TEST VOLTAGE VAC RMS AT 60 Hz
SEA LEVEL	750
ALTITUDE 70,000 FT (33.5 TORR) AMBIENT TEMP	250
ALTITUDE 80,000 FT (20.6 TORR) -50 °C TEMP	375

- CURRENT RATING : 1.5 AMPS
- UNLESS OTHERWISE SPECIFIED, TOLERANCES ARE: .XXX= .005 (.127) .XX = .02 (.51)

WEIGHT: .0040 Lbs. [1.814 gr.] MAX.

SPECIFICATION CONTROL DRAWING

DRAWN	Welch 2/9/84	Raychem <small>RAYCHEM CORPORATION 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025</small>		
CHECKED	M. H. [Signature] 2/13/84			
APPROVED	M. H. [Signature] 2/13/84	TITLE CABLE TRANSITION MODULE (CTM) FLAT TO FLAT TERMINATION, 40 CONDUCTOR, 2-INCH WITHOUT EARS, .050 PITCH ENVIRONMENT RESISTANT, 125 °C MAX. OPERATING TEMPERATURE		
APPROVED	[Signature] 2-13-84	SIZE	CODE IDENT. NO.	DWG. NO.
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. METRIC DIMENSIONS ARE IN PARENTHESIS		C	06090	CTM-1005
DO NOT SCALE THIS DRAWING		WEIGHT	SHEET 1 OF 1	