



WIRE LEADS 4.4 (111.8) MIN.
6.3 (160.0) MAX. 6° (152.4) TYP. LG.
NO. 26 AWG .009 (0.23) WALL PVC
RED: ANODE
BLACK: CATHODE
STRIPPED: .18/.32 (4.6/8.1)

MODEL NO.	COLOR	INCORPORATES LED NO.
5110F1	RED	4303F1
5110F1-12V	RED	4302F1-12V
5110F3	AMBER	4303F3
5110F5	GREEN	4303F5
5110F7	YELLOW	4303F7
5110F1LC	RED	4300F1LC
5110F5LC	GREEN	4300F5LC
5110F7LC	YELLOW	4300F7LC
5110F1-5V	RED	4302F1-5V
5110F3-5V	AMBER	4302F3-5V
5110F5-12V	YELLOW	4302F5-12V.
5110F5-5V	GREEN	4302F5-5V
5110F5-12V	GREEN	4302F5-12V
5110F6	BLUE	4302F6-LIBD
5110F1-5	RED/GRN	4301F1-5-A

NOTES:
1. MOUNTING HOLE .155/.158 (3.94/4.01) DIA.
IN PANELS .031/.062 (.79/1.58) THICK.

THIS DWG IS THE PROPERTY OF CHICAGO MINIATURE LAMP INC. AND IS PROPRIETARY IN GENERAL AND IN DETAIL. IT SHALL NOT BE COPIED OR ITS CONTENTS REVEALED TO OUTSIDE PARTIES WITHOUT THE WRITTEN CONSENT OF CHICAGO MINIATURE LAMP INC.

DO NOT SCALE

ORIGINAL WHEN RECD
OCT 10 2003
DIST. C

REV	ECR NO./DESCRIPTION	DATE
21483	RHW REDRAWN IN CAD.	
M	ADDED MODEL NO. 5110F3-12V. DWG. NO. WAS A7757.	04/05/02
21737	RHW ADDED MODEL NO. 5110F5-12V.	06/12/02
N	ADDED MODEL NO. 5110F5-12V.	
22883	RHW ADDED MODEL NO. 5110F1-12V.	
P	ADDED MODEL NO. 5110F1-12V.	10/06/03

FOR INSPECTION USE ONLY
 SPEC DOCUMENTATION REQ. (X R CHARTS)

PART NO. SEE TABLE
 MODEL NO. SEE TABLE
 QTY. 10
 FINISH:

TOLERANCE UNLESS OTHERWISE SPECIFIED:
 FRACTION ± 1/64
 DECIMALS .xxx ± .010 (0.25)
 ANGLES ± 1 deg.

CHICAGO MINIATURE LAMP INC.
 147 CENTRAL AVE. HICKENSACK, NJ 07801

DRAWN: R.H. M1991:ns
 CHECKED: *MM* 10/16/03
 BKG. APPROV: *LC*

TITLE: GLO-DOT 5110 SERIES INDICATOR LIGHT
 SCALE: NONE
 SHEET 1 OF 1