

Products

- Products Overview
- Product Search**
- Evaluate
 - FAQ's
- Design a Solution
 - Part Drawings
 - PDF-PVC Heat Shr
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Product Search >

Current refinements (click  to remove) Search Tips 

Part Number > HSTTP19-QY

Your search criteria matched only one product, shown below

HSTTP19-QY



PVC DRY-SHRINK™ Heat Shrink Tubing in Reels

- For dry locations
- Flexible, highly flame retardant tubing
- Good resistance to most fuels and oils
- Good cut through and solder resistance
- Material Type: Polyvinyl Chloride Cross-Linked
- Shrink Ratio: 2:1
- Temperature Range: -4°F to 221°F (-20°C to 105°C)
- Voltage: 600V
- UL VW-1 Recognized, CSA Certified
- For dry locations
- Flexible, highly flame retardant tubing
- Good resistance to most fuels and oils
- Good cut through and solder resistance

Part Number	HSTTP19-QY
RoHS Compliancy Status	Compliant
Note	HSTTP19-QY replaces HSTTP19-Q
Part Description	Flexible, Flame Retardant PVC material offers good cut through and solder resistance.
Material	Polyvinyl Chloride Cross-Linked
Color	Black
CSA Certified	Yes
UL Recognized	E122770
CE Compliant	No
Flammability Rating	UL224 VW-1
Length Per Reel (ft.)	25
Length Per Reel (m)	7.6
Max. Recovered I.D. (In.)	0.093
Max. Recovered I.D. (mm)	2.4
Min. Expanded I.D. (In.)	0.187
Min. Expanded I.D. (mm)	4.8
Nominal Diameter (In.)	0.187
Nominal Diameter (mm)	4.8
Nominal Recovered Wall Thickness (In.)	0.025
Nominal Recovered Wall Thickness (mm)	0.6
Pricing Description	Heat Shrink Thin PVC, .19"(4.8mm) Dia Black
Shrink Ratio	2:1
Temperature Range	-4°F – 221°F (-20°C – 105°C)
Min. Order UOM	RL
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	<input type="checkbox"/>

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.