



Grove - RTC

SKU 101020013

Description

The RTC module is a member of Twig. It is based on the clock chip DS1307 which supports the I2C protocol. It uses a Lithium cell battery (CR1225). The clock/calendar provides seconds, minutes, hours, day, date,month, and year information. The end of the month date is automatically adjusted for months with fewer than 31 days, including corrections for leap year. The clock operates in either the 24-hour or 12-hour format with AM/PM indicator.

Note: Battery is not included.

Features

- Real-Time Clock (RTC) counts seconds, minutes, hours, date of the month, month, day of the week, and year with Leap-Year compensation valid up to 2100
- 56-Byte, Battery-Backed, Nonvolatile (NV)RAM for data storage
- I2C serial interface
- 5V DC supply
- Programmable Square-Wave output signal
- Automatic Power-Fail detect and switch circuitry

• Consumes less than 500nA in Battery-Backup Mode with Oscillator Running

Documents

• For all Grove users (especially beginners), we provide you guidance PDF documents. Please download and read through Preface - Getting Started and Introduction to Grove before your using of the product.

Technical Details

Dimensions	130mm x 80mm x 10mm
Weight	G.W 10g
Battery	Exclude
Part List	
Grove - RTC	1
Grove Cable	1
ECCN/HTS	
ECCN	EAR99
HSCODE	9114909000
Certification	
RoHS	Compliant



