

Technical Data Sheet

Rev. B (4/20) Page 1 of 2

E-Line IPA Product# 1610-12S

Product Description

Introducing E-LINE IPA – Isopropyl Alcohol (IPA) in new, convenient aerosol packaging. 99+% pure anhydrous (minimal water) IPA is excellent for defluxing, fiber optics maintenance, stencil cleaning, tool cleaning, tape-head cleaning and other light-duty cleaning.


Flux removers (defluxers) remove flux residues and other contaminants left by manufacture, rework, or repair of printed circuit boards. Residues from higher, lead free temperatures are more baked on and harder to clean. Techspray® flux removers have been proven very effective at removing fluxes baked on at lead free temperatures.

Features / Benefits

- 99+% pure IPA
- Compliant with SCAQMD rule 1171
- Ideal for defluxing, stencil cleaning & fiber optics
- Plastic safe
- Low toxicity
- Non-ozone depleting
- NSF registered K1 and K2

Usage Instructions

Disconnect equipment from power source. Make sure opening of sprayhead is pointing toward surface to be cleaned. Hold can 6-8 inches away. Direct spray to saturate soiled surface. For defluxing or stencil cleaning, use with low linting **Techclean** wipes (e.g. 2350-100). When used as a general cleaner, start at top of area to be cleaned using a sweeping motion and spray the area, slowly working toward the bottom. To clean in hard to reach areas, insert extension tube in sprayhead to direct spray. Allow components to dry completely before applying current.



Typical Product Data and Physical Properties

| Physical State: | Liquid |
|------------------------|----------------------------|
| Odor: | Alcohol odor |
| Appearance: | Clear, Colorless liquid |
| pH: | Neutral |
| Percent Volatile: | 100 |
| Vapor Pressure: | 33 mmHg at 20°C |
| Vapor Density: | 2.07 (Air=1) |
| Boiling Point: | to 180°F (82°C) |
| Freezing Point: | to -126°F (-88°C) |
| Flashpoint and Method: | 53°F (11.7°C) TAG CC |
| Solubility in water: | Miscible |
| Evaporation rate: | to 1.7 (n-Butyl Acetate=1) |
| Specific gravity: | 0.783-0.787 (water=1) |
| VOC: | 75% by weight (EPA) |
| Shelf life: | 5 years unopened |



Technical Data Sheet

Rev. B (4/20) Page 2 of 2

E-Line IPA Product# 1610-12S

Packaging and Availability

1610-12S 12 oz. (340g)

1610-400S 12 oz. (340g) EU labeled

Environmental Policy

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Resources

Techspray® products are supported by global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.echspray.com.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



Techspray® 8125 Cobb Center Drive Kennesaw, GA 30152 800-858-4043 tsales@techspray.com

Europe

ITW Contamination Control BV Saffierlaan 5, 2132 VZ Hoofddorp The Netherlands +31 88 1307 400 info@itw-cc.com

Countries outside the US Call to locate a distributor in your country