



### PRODUCT FEATURES

- Extend data up to 1.2 km (4,000 ft.)
- 2 kV optical isolation on input/output
- Wide operating temperature (-40 to +80 °C)
- 115.2 kbps data rate
- Modbus compatible

The 485LDRC is an optically isolated RS-232 to RS-422/485 converter. RS-232 signals interface through a terminal block. RS-422/485 signals and power inputs connect to the terminal block. Terminal blocks are arranged to allow easy wiring inside a control panel.

Built-in Automatic Send Data Control circuitry allows quick set-up and eliminates the need for external software drivers to control handshake signals. The converter operates on externally sourced 10-30 VDC power.

Optically isolated data lines (2,000 V on input/output) with 500W surge suppression ensure that connected equipment is protected even in the harshest environments. DIN rail mount design snaps on standard 35mm rail and a small form factor fits neatly into tight cabinets.

The 485LDRC is ideal for critical industrial communications, factory automation, in-cabinet conversion, warehouse automation, security, and many other applications.

### ORDERING INFORMATION

MODEL NUMBER	RS-232 CONNECTOR	RS-422/485 CONNECTOR
485LDRC	Terminal Block	Terminal Block

### ACCESSORIES

MDR-20-24 - PS, DIN, Slim, Plastic, 24W, 24V

### SPECIFICATIONS

#### SERIAL TECHNOLOGY

<b>Data Rate</b>	115.2 kbps
<b>RS-232 - 2 options</b>	
Connector	Terminal block
Signals	TD, RD, GND
<b>RS-422</b>	
Connector	Terminal block
Signals	TDA(-), TDB(+), RDA(-), RDB(+), GND
Termination	120 (switchable)
<b>RS-485</b>	
Connector	Terminal Block
Signals	TDA(-), TDB(+), RDA(-), RDB(+), GND
Modes	2-wire and 4-wire
Termination	120 Ohm (switchable)

#### ISOLATION

Lines Protected	Data lines
Method	Optical
Rating	2,000 V

#### SURGE SUPPRESSION

Lines Protected	Data lines
Method	TVS
Rating	7.5V bi-directional avalanche breakdown device 500W peak power dissipation
Response Time	< 1 pico-second

#### INDUSTRIAL BUS

Modbus	ASCII/RTU
--------	-----------

All product specifications are subject to change without notice.  
485LDRC\_0917ds

# Industrial Isolated Converter

## 485LDRC



### SPECIFICATIONS - CONTINUED

#### POWER

Connector	Terminal block
Voltage	10-30 VDC
Consumption	0.5 W
Source	External powering required

#### TERMINAL BLOCKS

Wire Size	24 to 14 AWG
Torque	4 kfg-cm

#### LED INDICATORS

Power (RED)	On when power applied
TD (RED)	Flashes when RS-422/485 data is transmitted
RD (RED)	Flashes when RS-422/485 data is received

#### ENCLOSURE

Material	Plastic
IP Rating	20
Dimensions	2.5 x 7.9 x 9.5 cm (1.0 x 3.1 x 3.7 in)
Mounting	35 mm DIN rail (panel mount adapter available)

#### ENVIRONMENTAL

Operating Temperature	-40 to +80 °C (-40 to +176 °F)
Storage Temperature	-40 to +85 °C (-40 to +185 °F)
Operating Humidity	0 to 95% non-condensing
MTBF	257448 hours
MTBF Calculation Method	MIL 217F Parts Count Reliability Prediction

#### APPROVALS / CERTIFICATIONS

2004/108/EC	Electromagnetic Compatibility Directive
2011/65/EU	Reduction of Hazardous Substances Directive
EN 55022: +AC	Information technology equipment - Class A RF Emissions
EN 55024	Information technology equipment - Immunity (Light-industrial Environments)
EN 61000-4-2	ESD Immunity
EN 61000-4-3: +A2	Radiated Field Immunity (RFI)
EN 61000-4-4	EFT/Burst Immunity
EN 61000-4-5	RF Conducted Immunity

### MECHANICAL DIAGRAM

