



### Main

Range of product	Harmony Electromechanical Relays
Product or component type	Socket
Product compatibility	Relay 792XDX relay 782XDXH
Number of terminals	14
Switch function	4PDT
Contacts type and composition	4 C/O

### Complementary

[In] rated current	10 A
[Ue] rated operational voltage	300 V
Contact terminal arrangement	Mixed
Connections - terminals	Panel screw clamp terminals, clamping connection capacity: 2 x 1.5...2 x 2.5 m <sup>2</sup> , AWG 16...AWG 14 solid for output Panel screw clamp terminals, clamping connection capacity: 2 x 1.5...2 x 2.5 m <sup>2</sup> , AWG 16...AWG 14 stranded for output
Tightening torque	Chassis: 0.8 N.m, AWG 16...AWG 14, copper Screw: < 0.8 N.m
Fixing mode	By screws, M3, for panel
Shape of screw head	Combination roundhead
Product weight	50 G
Width	30.7 Mm
Depth	64 Mm

### Environment

Ambient air temperature for storage	-40...105 °C
Ambient air temperature for operation	-40...70 °C
Flame retardance	UL94-V0
Product certifications	UL CSA CE

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.9 Cm
Package 1 Width	3.07 Cm
Package 1 Length	2.54 Cm
Package 1 Weight	50 G

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

Product Life Status : **Commercialised**