



JKL PART NUMBER	LENGTH A +/- 2mm	COLOR (REF.)	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF5118-20B	118mm	RGB HIGH OUTPUT WHITE 5400° KELVIN	600	305	5 ± 1	7000 ± 700	20,000
BF5165-20B	165mm		800	400	5 ± 1	7000 ± 700	20,000
BF5200-20B	200mm		850	445	5 ± 1	7000 ± 700	20,000
BF5300-20B	300mm		1000	600	5 ± 1	7000 ± 700	20,000

\*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

		<b>METRIC</b> DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		<b>JKL COMPONENTS CORPORATION</b>			
				<b>TITLE</b> SINGLE LEAD TIPLESS MINIATURE FLUORESCENT LAMP			
<b>DRAWN BY</b> L. WENGSTROM		<b>APPV'D BY</b> JK		<b>DATE</b> 02/29/00		<b>SIZE</b> A	
<b>RELEASED - CANCEL BF-5mm DIA DRAWING</b>		<b>DATE</b> 2/25/00		<b>FSCM NO.</b> 55335		<b>DRAWING NO.</b> BF 5-20B	
<b>REV. NO.</b>		<b>DESCRIPTION/ECO NUMBER</b>		<b>SCALE</b> NONE		<b>RELEASED DATE</b> 2/25/00	
		<b>APPV'D DATE</b>		<b>REVISION DATE</b> 2/29/00		<b>REV. NO.</b> A	
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED				<b>SHEET</b> 1 of 1			