2-171825-4 - ACTIVE

TE Internal #: 2-171825-4 PCB Mount Header, Vertical, Wire-to-Board, 4 Position, 5 mm [.197 in] Centerline, Partially Shrouded, Tin, Through Hole - Solder, Signal, Black

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles



Connector System: Wire-to-Board

Number of Positions: **4**

Number of Rows: 1

Centerline (Pitch): 5 mm [.197 in]

PCB Mount Orientation: Vertical

Features

Product Type Features

Connector System	Wire-to-Board
Header Type	Partially Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

PCB Connector Assembly Type	PCB Mount Header	
Configuration Features		
Number of Positions	4	
Number of Rows	1	
PCB Mount Orientation	Vertical	
Electrical Characteristics		
Operating Voltage	250 VAC	
Body Features		
Connector Profile	Low	
Primary Product Color	Black	
Contact Features		
Contact Mating Area Length	7.5 mm[.295 in]	
Mating Square Post Dimension	.64 mm[.025 in]	
PCB Contact Termination Area Plating Material Thickness	.8 μm	

PCB Mount Header, Vertical, Wire-to-Board, 4 Position, 5 mm [.197 in] Centerline, Partially Shrouded, Tin, Through Hole - Solder, Signal, Black



Contact Mating Area Plating Material Thickness	.8 μm[31.49 μin]	
Contact Shape & Form	Square	
PCB Contact Termination Area Plating Material	Tin	
Contact Base Material	Brass	
Contact Mating Area Plating Material	Tin	
Contact Type	Pin	
Contact Current Rating (Max)	5 A	
Termination Features		
Square Termination Post & Tail Dimension	.64 mm[.025 in]	
Termination Post & Tail Length	3.6 mm[.142 in]	
Termination Method to Printed Circuit Board	Through Hole - Solder	
Mechanical Attachment		
Mating Alignment Type	Polarization	
Mating Retention	With	
Panel Mount Feature	Without	
PCB Mount Retention Type	Retention Solder Tails	
Mating Retention Type	Polarized Lock	
Connector Mounting Type	Board Mount	
Mating Alignment	With	
PCB Mount Alignment	Without	
PCB Mount Retention	With	
Housing Features		
Housing Material	6/6 Nylon	
Centerline (Pitch)	5 mm[.197 in]	
Dimensions		
Connector Length	10 mm[.394 in]	
Connector Height	10.4 mm[.409 in]	
PCB Thickness (Recommended)	1.6 mm[.063 in]	
Usage Conditions		
Operating Temperature Range	-20 – 95 °C[-4 – 203 °F]	
Operation/Application		
Circuit Application	Signal	

PCB Mount Header, Vertical, Wire-to-Board, 4 Position, 5 mm [.197 in] Centerline, Partially Shrouded, Tin, Through Hole - Solder, Signal, Black



Industry Standards

Agency/Standard	UL
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	1000
Packaging Type	Bag, Box

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

PCB Mount Header, Vertical, Wire-to-Board, 4 Position, 5 mm [.197 in] Centerline, Partially Shrouded, Tin, Through Hole - Solder, Signal, Black





Customers Also Bought



1.0 FPC, ZIF V/T, SMT, 8P

EIS REC. HSG 7P-NATURAL	1MM FFC SMT V ASSY 10P EMBOSS	1.0 FPC, ZIF V/T, SMT, 10P
TE Part #3-2176230-9 3522 1K2 5% 3W	TE Part #171825-4 TYPE V EIS CONNECTOR 4P ASSY	

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-171825-4_Y2.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-171825-4_Y2.3d_igs.zip

English

PCB Mount Header, Vertical, Wire-to-Board, 4 Position, 5 mm [.197 in] Centerline, Partially Shrouded, Tin, Through Hole - Solder, Signal, Black



Customer View Model

ENG_CVM_CVM_2-171825-4_Y2.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages 1-1773972-5_EIS_Connectors_Brochure

English

Product Specifications

Crimping of AMP El Series Connector Contacts

Japanese

Application Specification

Japanese

Agency Approvals Agency Approval Document

English