


Insulation Thickness 0.76mm  
Overall Diameter 3.6±0.10mm

Copper Conductor  
41/0.26±0.004mm  
Resistance 8.88  
(20° (Max). ohms/km)

Jacket Thickness 0.76mm  
Overall Diameter 9.3±0.15mm



Green

Black

White

(Wire Cross-Section)

Plug Component			Plug Strip Dimension			Wire Spec.	Terminal ROJ & Strip		
Color	Component	Qty	Strip	ROJ	Color		Strip	ROJ	Color
40P Black 90±5° A	LT-202(15A 125V) (NEMA5-15P)	1	7±1	23±3	Black	SJT 14AWGX3C 105°C BLACK  Length: 2000±50 mm	5/8" (16mm)	2" (50.8mm)	Black
Nickel-Plated	Plug Terminal	1	7±1	23±3	White		5/8" (16mm)	2" (50.8mm)	White
Nickel-Plated	UL Blades	2	7±1	26±3	Green		5/8" (16mm)	2" (50.8mm)	Green
White	(202 Inner Body)	1							

**NOTE :**

1. PLUG : LT-202 AMERICAN TYPE
2. CONNECTOR : NA
3. CORD : SJT 14AWGX3C 105°C BLACK 2M
4. APPROVALS : UL C-UL
5. Supplier for flexible cord : RHYTHM
6. Hi-Pot Test:2000v/1min<1mA>

**Marking:**

RHYTHM: (UL) E88231 SJT 3X14AWG(2.08mm<sup>2</sup>)  
105°C 300V VW-1 CSA LL54496 SJT  
3X14AWG(2.08mm<sup>2</sup>)105°C 300V VW-1  
RHYTHM R

**Modification History**

NO.	DESCRIPTION	DATE

<b>DRAWER</b>	Eric	<b>DATE</b>	20/10/17	<b>P/N</b>	800-1401-2-SJT0-BL-00200-1
<b>APPROVE</b>		<b>REV.</b>	0	<b>Dr.No.</b>	1091055
		<b>TOL.</b>			±5mm
		<b>ALL DIMENSIONS IN mm</b>			
			比例		

**CnC Tech**  
Industrial Cable and Connector Technology