



Product summary

EVK-M9DR


u-blox M9 GNSS dead reckoning evaluation kit

For evaluation of M9 ADR and UDR features

- USB (Type-C connector) available for power supply and data transfer
- Supercap, CR2032 battery, and micro USB port for backup power supply
- 14-pin front connector to access all interfaces



105 x 64 x 26 mm



Experience u-blox GNSS performance in 4 simple steps

Step 1	On a PC with a USB interface, download and install the u-center evaluation software: www.u-blox.com/product/u-center
Step 2	Connect the EVK-M9DR to the PC with the USB cable. Microsoft USB driver for Windows 10 installs automatically via Windows Update. The u-blox USB driver for Windows 7 and 8 is available in the u-center installation package.
Step 3	Connect the antenna.
Step 4	Start the u-center evaluation tool.

Product description

The EVK-M9DR evaluation kit is perfect for evaluation and performance analysis of the u-blox M9 positioning dead reckoning technology. The built-in Type-C USB interface provides both power supply and high-speed data transfer, as well as improved retention force of the connector, which makes the evaluation easier compared to previous EVK generations. EVK-M9DR also includes a supercap, a CR2032 battery holder, and a micro USB port to power V_BCKP in the event of VCC outage, preserving the contents of the battery-backed RAM (BBR) and allowing faster warm/hot starts.

The compact u-blox EVK-M9DR evaluation kit comes in rugged metal housing. The user-friendly interface and V_BCKP power supply option make it ideally suited for use in laboratories, test vehicles (drive testing) and outdoor locations. Used with a PDA or a notebook PC, it is a perfect companion through all design stages of projects.

Kit includes

- EVK-M9DR unit
- Type-C USB cable
- Micro USB cable
- Active GNSS antenna with 3 m cable

Features

- Type-C USB cable for easy connection to PC
- 14-pin connector for access to interface pins
- 9-pin D-SUB female connector for standard RS232 interface
- Switch to select between the I2C (and RS232) and SPI communications interfaces
- LED to indicate power supply and GNSS operation
- Reset (RST) button to restart the unit
- SMA connector for connection to antenna or simulator
- Carrier phase RAW data

Documentation

Visit www.u-blox.com/product/evk-m9dr to find related documentation.

Product variants

EVK-M9DR	u-blox M9 GNSS DR evaluation kit supports UBX-M9340-KB, UBX-M9140-KA-DR chips and NEO-M9L, NEO-M9V modules
----------	--

Legal Notice:

u-blox or third parties may hold intellectual property rights in the products, names, logos and designs included in this document. Copying, reproduction, or modification of this document or any part thereof is only permitted with the express written permission of u-blox. Disclosure to third parties is permitted for clearly public documents only.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com.

Copyright © 2023, u-blox AG

Further information

For contact information, see www.u-blox.com/contact-u-blox.