

Han-Modular Flexbox hood 3 entries



Part number	09 14 000 8013
Specification	Han-Modular Flexbox hood 3 entries
HARTING eCatalogue	https://b2b.harting.com/09140008013

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Hoods/Housings
Series of hoods/housings	Han-Modular [®] Flexbox
Type of hood/housing	Hood
Version	
Version	Top entry
Cable entry	3x
Technical characteristics	
Limiting temperature	-40 +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP54
Clamping range	5 24 mm
Material properties	
Material (hood/housing)	Polyamide (PA) Fibre-glass reinforced
Colour (hood/housing)	RAL 9005 (jet black)
Material (seal)	NBR
Colour (seal)	RAL 9005 (jet black)

	RAL 9005 (Jet black)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant

Page 1 / 2 | Creation date 2023-06-17 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Material properties

China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)

Specifications and approvals

	IEC 61984
Specifications	EN 45545-1
	EN 45545-2

Commercial data

Packaging size	1
Net weight	109.6 g
Country of origin	China
European customs tariff number	85389099
GTIN	5713140182011
eCl@ss	27440202 Shell for industrial connectors