





APPROVED: \_\_\_\_\_  
 DATE: \_\_\_\_\_ TITLE: \_\_\_\_\_

Rev	AWO #	Description	Date	Appr
-		RELEASED	11/22/10	
A		REDRAWN	08/30/12	



Panel hole dimensions



**SPECIFICATIONS:**

**Material:**  
 Insulator: Nylon66, rated UL94V-2  
 Insulator color: Natural

**Electrical:**  
 Current rating: 13A  
 Voltage rating: 600V  
 Insulation resistance: 1000 Mohms min  
 Dielectric withstanding voltage: 5000 VAC for 1 minut  
 Temperature range: -55°C to +105°C

**Environmental:**  
 Lead free, RoHS compliant.



UNLESS OTHERWISE SPECIFIED  
 ALL DIMENSIONS ARE INCHES [MM]  
 TOLERANCES: EXCEPT AS NOTED

INCHES	HOLES
.X ± .10	ØX ± .10
.XX ± .020	ØXX ± .015
.XXX ± .015	ØXXX ± .010

**ADAM TECH**  
 909 Rahway Avenue, Union, NJ 07083  
 Phone: 908-687-5000 Fax: 908-687-5710

APPROVALS		TITLE	
DRAWN	DY	11/22/10	6.35MM PITCH CONNECTOR, SINGLE ROW HOUSING, MALE, 4 POSITION
CHECKED			
APPROVED			

REF:	SIZE	PART NO.	SCALE:	SHEET	REV.
S00123T	X	DME-M-04	NTS	1 OF 1	A