



Que-2-TXT™
Questions?
scan to text us fast



LINEAR BATTEN LED LAMP



HIGH OUTPUT LINKABLE

fluorescent equal

specifications

Consumption	Lumen Output	Efficacy	Voltage	Lens	Heat Sink	L70 hours	Ambient Temp (F)	Power Factor	UL listing	CRI	THD	Dimensions
30W	3,750	125 LM/W	100-277 V	polycarbonate	aluminum	50,000	-4° - 113°	>0.9	IP40	83	<20%	44.23" x 1.61" x 1.41"

select your lamp

Part Number	Color Temp	
GI-4DT5D-W60-BF	3000K	frosted cover
GI-4DT5D-D60-BF	4000K	frosted cover
GI-4DT5-D60-BC	4000K	clear cover
GI-4DT5-C60-BC	5000K	clear cover



add your accessories*

Accessories Part Number	
GI-ACC-3PC	3' power cable with plug
GI-ACC-6PC	6' power cable with plug
GI-ACC-15CC	1.5' linking cable
GI-ACC-6CC	6' linking cable
GI-ACC-SUS-DT5	suspension kit
GI-ACC-MC-T8	magnetic clip

*optional

other


Warranty	Weight	Case QTY
6 years	1.32 lbs	20 pcs




Features

- > Linkable up to 200W.
- > Aluminum housing allows for excellent heat dissipation.
- > 50,000 hour LED lifespan based on IES LM-80 results and TM-21 calculations.
- > Patent Male-female linkable design.

Light Distribution Curve



Lux vs Distance



Not all product variations listed on this page may be DLC qualified. Visit www.designlights.org/search to confirm qualification.



/greenignite
@greenignite



www.greenignite.com



info@greenignite.com



1-877-560-3779