



Bayonet Channel x 3

Protective Cap  
(Bayonet Locking Type)

Tether

(b)

(c)

**Notes:**

- 1. Material:
  - Protective Cap: PBT(Black); UL94 V-0
  - Tether: PE (Black)
- Operating Temperature: -40°C to +85°C

|  |             |       |            |      |  |                    |  |                 |   |  |
|--|-------------|-------|------------|------|--|--------------------|--|-----------------|---|--|
| THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH<br><br>DO NOT ALTER CAD DRAWING BY HAND |             |       |            |      | Tolerance<br>Unless otherwise specified<br>0. ±0.50<br>0.0 ±0.38<br>0.00 ±0.25<br>Angles ±3° |                    | dim. in mm   |                 | scale: 2:1 (1,5:1)<br>material: see notes |  |
|  |             |       |            |      | date name<br>drawn 05.11.13 Strakerjahn<br>appd. 05.11.13 Koch                               |                    | title:<br>(d) Protective Cover<br>for IP67 Duplex Power 2+3pos<br>Male Receptacle Assembly |                 |   |  |
|  | 1 x d       | Ä6182 | 06.06.2016 | K.H. | norm   |                    |  |                 |   |  |
|  | 3 x c       | Ä5616 | 21.04.15   | K.H. | d-old  |                    |  |                 |   |  |
|  | 1 x b       | Ä5593 | 30.03.2015 | K.H. |  |                    |  |                 |   |  |
| a  | Original    |       |            |      |  |                    |  |                 |   |  |
| rev.   | description | date  | name       |      |  | dwg no: 17K1A430   |  | DIN-A3<br>sh: 1 |   |  |
|  |             |       |            |      |  | part no: 17-400260 |  |                 |   |  |

RoHS compliant