

“Stay Connected” with



HEYware Products

a PennEngineering® Company





- For clamping cable or tubing securely into place, especially in **harsh environments**.
- Smooth “coined clamp” edges prevent damage to cable insulation.
- Constructed from corrosion resistant 304 stainless steel.
- Coated parts are constructed from 304 stainless steel and coated with polyolefin a thermoplastic co-polymer.
- Coating provides a durable non-toxic, odorless coating that has very good low temperature flexibility and excellent electrical properties. This coating also has **FDA food contact** approval.
- All parts require a .203” (5,2 mm) mounting hole suitable for a #10 screw.
- Not for use in a marine salt water environment. Contact Heyco for alternative materials.
- DFARS Compliant

Heyco® Stainless Steel Cable Clamps

PART DIMENSION A			STANDARD		COATED	
in.	mm.	PART NO.	DESCRIPTION	PART NO.	DESCRIPTION	
.19	4,7	S3373	CC H 3/16 SS	S3323	CC H 3/16 SS Coated	NEW!
.25	6,3	S3374	CC H 1/4 SS	S3324	CC H 1/4 SS Coated	
.38	9,5	S3376	CC H 3/8 SS	S3326	CC H 3/8 SS Coated	
.50	12,7	S3378	CC H 1/2 SS	S3328	CC H 1/2 SS Coated	
.63	15,9	S3380	CC H 5/8 SS	S3330	CC H 5/8 SS Coated	
.75	19,1	S3382	CC H 3/4 SS	S3332	CC H 3/4 SS Coated	
.88	22,2	S3384	CC H 7/8 SS	S3334	CC H 7/8 SS Coated	

Consult Heyco for additional sizes.




Heyco® Steel Cushion Clamps

MOUNTING HOLE DIA.		SCREW SIZE	PART DIMENSION A		PART NO.	DESCRIPTION
in.	mm.		in.	mm.		
.650” (16,5 mm) Overall Width, .031” (0,8 mm) Steel Thickness						
.265	6,7	1/4	0.19	4,7	12300	CCSC L 3/16
			0.25	6,3	12301	CCSC L 1/4
			0.31	7,9	12302	CCSC L 5/16
			0.38	9,5	12303	CCSC L 3/8
			0.44	11,1	12304	CCSC L 7/16
			0.50	12,7	12305	CCSC L 1/2
			0.56	14,3	12306	CCSC L 9/16
			0.63	15,9	12307	CCSC L 5/8
			0.69	17,4	12308	CCSC L 11/16
			0.75	19,1	12309	CCSC L 3/4
			0.88	22,2	12310	CCSC L 7/8
			1.00	25,4	12311	CCSC L 1
			1.13	28,6	12312	CCSC L 1-1/8
			1.25	31,8	12313	CCSC L 1-1/4
			1.50	38,1	12314	CCSC L 1-1/2
			2.00	50,8	12315	CCSC L 2
2.50	63,5	12316	CCSC L 2-1/2			
3.00	76,2	12317	CCSC L 3			
.750” (19,1 mm) Overall Width, .047” (1,2 mm) Steel Thickness						
.406	10,3	7/16	0.25	6,3	12331	CCSC H 1/4
			0.31	7,9	12332	CCSC H 5/16
			0.38	9,5	12333	CCSC H 3/8
			0.44	11,1	12334	CCSC H 7/16
			0.50	12,7	12335	CCSC H 1/2
			0.63	15,9	12337	CCSC H 5/8
			0.69	17,4	12338	CCSC H 11/16
			0.88	22,2	12340	CCSC H 7/8
			1.00	25,4	12341	CCSC H 1
			1.25	31,8	12343	CCSC H 1-1/4
			1.50	38,1	12344	CCSC H 1-1/2
			2.00	50,8	12345	CCSC H 2
			2.50	63,5	12346	CCSC H 2-1/2
			3.00	76,2	12347	CCSC H 3



- Light to heavy duty steel clamp.
- E.P.D.M. cushion for electrical insulation and vibration absorption.
- Steel clamps are zinc electroplated for corrosion resistance.
- Color - Silver with durable black cushion.



Quick Specs

Material	CC H 304 Stainless Steel	CCSC Zinc Plated Steel with a UV resistant EPDM Sleeve
Temperature Range	0°C (32°F) to 60°C (140°F)	-40°C (-40°F) to 100°C (212°F)