

more than you expect



Application Guide inside!

Interface Design Kit for USB, CAN, Ethernet, VGA, DVI, RS232, RS485

Order Code 744 999
Version 1.0

more than you expect



Application Guide inside!

Interface Design Kit for USB, CAN, Ethernet, VGA, DVI, RS232, RS485

Order Code 744 999
Version 1.0

Interface Design Kit for USB, CAN, Ethernet, VGA, DVI, RS232, RS485



ESD Suppressor WE-VE 823 56 120 100 V_{DC} : 12 V C : 10 pF (1MHz) V_C : 60 V (1 A, 8/20 μ s) $I_{L,max}$: 1 μ A (V_{DC}) Size 0603	SMD Common Mode Choke WE-CNSW 744 232 222 $Z @ 100$ MHz: 2200 Ω DCR: 1.2 Ω Rated current: 200 mA Size 1206	Chip Bead Ferrite WE-CBF 742 792 040 $Z @ 100$ MHz: 600 Ω DCR: 0.15 Ω Rated current: 200 mA Z max: 700 $\Omega @ 150$ MHz Size 0805	USB Type A Connector WE-COM 614 004 160 21 No. of Pins: 4 Rated current: 1 A Operating voltage: 30 V THT	USB Type B Connector WE-COM 614 004 161 21 No. of Pins: 4 Rated current: 1 A Operating voltage: 30 V THT	ESD Suppressor WE-VE 823 56 050 050 V_{DC} : 5 V C : 5 pF (1MHz) V_C : 34 V (1 A, 8/20 μ s) $I_{L,max}$: 1 μ A (V_{DC}) Size 0603	SMD Common Mode Choke WE-CNSW 744 231 371 $Z @ 100$ MHz: 370 Ω DCR: 0.45 Ω Current: 280 mA Size 0805
ESD Suppressor WE-VE 823 56 050 220 V_{DC} : 5 V C : 22 pF (1MHz) V_C : 34 V (1 A, 8/20 μ s) $I_{L,max}$: 1 μ A (V_{DC}) Size 0603	SMD Common Mode Choke WE-SLM 744 242 510 Z max: 800 Ω L : 2x51 μ H DCR: 0.32 Ω Rated current: 300 mA	SMD Filter Inductor WE-GF 744 764 004 L : 0.47 μ H DCR: 0.50 Ω Rated current: 450 mA SRF: 220 MHz Size 1210	Terminal Block WR-TBL 691 401 710 004 No. of Pins: 4 AWG: 14-24 Pitch: 5 mm Rated current: 10 A Operating voltage: 300 VAC	Terminal Block WR-TBL 691 412 120 004 No. of Pins: 4 AWG: 16-20 Pitch: 3.5 mm Rated current: 6 A Operating voltage: 300 VAC	ESD Suppressor WE-VE ULC 823 07 050 029 V_{DC} : 5 V C : 0.2 pF (1MHz) V_C : 17 V (30ns, contact) $I_{L,max}$: 0.1 μ A (V_{DC}) Size 0402	SMD Common Mode Choke WE-CNSW 744 232 090 $Z @ 100$ MHz: 90 Ω DCR: 0.30 Ω Rated current: 370 mA Size 1206
ESD Suppressor WE-VE 823 56 240 030 V_{DC} : 24 V C : 3 pF (1MHz) V_C : 200 V (1 A, 8/20 μ s) $I_{L,max}$: 1 μ A (V_{DC}) Size 0603	LAN Transformer 10/100 BaseT WE-LAN 749 010 012 Size 12.10 x 5.20 x 9.53 IL: 1-100 MHz / -1.1dB max RL: 1-80 MHz / -16 dB to -10 dB DCMRR: 30-100 MHz / -38 dB to -30 dB	LAN Transformer Gigabit WE-LAN 749 020 010 Size 17.30 x 6.50 x 16.00 IL: 1-100 MHz / -1.0 dB max RL: 1-100 MHz / -1 dB to -10 dB DCMRR: 30-100 MHz / -43 dB to -33 dB	RJ45 Modular Jack WR-COM 615 008 142 21 No. of Pins: 8 Rated current: 1.5 A Operating voltage: 120 VAC Shielded, Receptable THT	LAN RJ45 100 Base-T Transformer 749 921 1123 100 Base-T Tab down LED yellow - green Integrated magnetics	DVI Connector WR-COM 675 024 321 221 No. of Pins: 24 + 1 Rated current: 3 A Operating voltage: 40 V Shielded, Receptable, THT Digital	ESD Suppressor WE-VE femtoF 823 16 14 V_{DC} : 14 V C : 0.05 pF (1 MHz) V_C : 50 V (30ns, contact) $I_{L,max}$: 0.001 μ A Size 0603
ESD Suppressor WE-VE ULC 823 06 120 029 V_{DC} : 12 V C : 0.2 pF (1MHz) V_C : 30 V (30ns, contact) $I_{L,max}$: 0.1 μ A Size 0603	Chip Bead Ferrite WE-CBF 742 792 041 $Z @ 100$ MHz: 600 Ω DCR: 0.40 Ω Rated current: 500 mA Z max: 700 $\Omega @ 1600$ MHz Size 0805	Chip Bead Ferrite WE-CBF 742 792 60 $Z @ 100$ MHz: 40 Ω DCR: 0.15 Ω Rated current: 400 mA Z max: 60 $\Omega @ 1000$ MHz Size 0603	MiniDIN Connector WR-COM 631 004 112 021 No. of Pins: 4 Rated current: 1 A Operating voltage: 12 V Shielded, Receptable, THT	D-SUB Socket WR-DSUB 618 015 325 223 No. of Pins: 15 Rated current: 3 A Operating voltage: 125 VAC High Density Female	DVI Connector WR-COM 675 024 321 321 24 + 5 Rated current: 3 A Operating voltage: 40 V Shielded, Receptable, THT Analog & Digital	Evaluation Board for Chip Bead Ferrits and Common Mode Chokes EP-CBF-0805 EP-CBF-1206 EP-Stroko
ESD Suppressor WE-VE 823 56 120 100 V_{DC} : 5 V C : 100 pF (1MHz) V_C : 30 V (1 A, 8/20 μ s) $I_{L,max}$: 1 μ A (V_{DC}) Size 0603	Chip Bead Ferrite WE-CBF 742 792 094 $Z @ 100$ MHz: 2200 Ω DCR: 0.60 Ω Rated current: 200 mA Z max: 3000 $\Omega @ 80$ MHz Size 0805	D-SUB Connector 618 009 248 23 No. of Pins: 9 Rated current: 3 A Operating voltage: 250 VAC Male	D-SUB Socket WR-DSUB 618 009 211 821 No. of Pins: 9 Rated current: 3 A Operating voltage: 250 VAC Female	Terminal Block WR-TBL 691 102 710 003 No. of Pins: 3 AWG: 14-22 Pitch: 5 mm Rated current: 15 A Operating voltage: 300 VAC	Terminal Block WR-TBL 691 212 710 002 No. of Pins: 2 AWG: 12-22 Pitch: 5 mm Rated current: 10 A Operating voltage: 300 VAC	Ethernet Evaluation Board Evaluation Board for Ethernet (RJ45 / integrated connector) performance testing

Applications

- USB 1.0
- USB 1.1
- USB 2.0
- CAN
- Ethernet
- VGA
- RS232
- RS485
- DVI

Please check datasheets on www.we-online.com for specifications. Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions. © 2009

www.we-online.com

Interface Design Kit for USB, CAN, Ethernet, VGA, DVI, RS232, RS485



ESD Suppressor WE-VE 823 56 120 100 V_{DC} : 12 V C : 10 pF (1MHz) V_C : 60 V (1 A, 8/20 μ s) $I_{L,max}$: 1 μ A (V_{DC}) Size 0603	SMD Common Mode Choke WE-CNSW 744 232 222 $Z @ 100$ MHz: 2200 Ω DCR: 1.2 Ω Rated current: 200 mA Size 1206	Chip Bead Ferrite WE-CBF 742 792 040 $Z @ 100$ MHz: 600 Ω DCR: 0.15 Ω Rated current: 200 mA Z max: 700 $\Omega @ 150$ MHz Size 0805	USB Type A Connector WE-COM 614 004 160 21 No. of Pins: 4 Rated current: 1 A Operating voltage: 30 V THT	USB Type B Connector WE-COM 614 004 161 21 No. of Pins: 4 Rated current: 1 A Operating voltage: 30 V THT	ESD Suppressor WE-VE 823 56 050 050 V_{DC} : 5 V C : 5 pF (1MHz) V_C : 34 V (1 A, 8/20 μ s) $I_{L,max}$: 1 μ A (V_{DC}) Size 0603	SMD Common Mode Choke WE-CNSW 744 231 371 $Z @ 100$ MHz: 370 Ω DCR: 0.45 Ω Current: 280 mA Size 0805
ESD Suppressor WE-VE 823 56 050 220 V_{DC} : 5 V C : 22 pF (1MHz) V_C : 34 V (1 A, 8/20 μ s) $I_{L,max}$: 1 μ A (V_{DC}) Size 0603	SMD Common Mode Choke WE-SLM 744 242 510 Z max: 800 Ω L : 2x51 μ H DCR: 0.32 Ω Rated current: 300 mA	SMD Filter Inductor WE-GF 744 764 004 L : 0.47 μ H DCR: 0.50 Ω Rated current: 450 mA SRF: 220 MHz Size 1210	Terminal Block WR-TBL 691 401 710 004 No. of Pins: 4 AWG: 14-24 Pitch: 5 mm Rated current: 10 A Operating voltage: 300 VAC	Terminal Block WR-TBL 691 412 120 004 No. of Pins: 4 AWG: 16-20 Pitch: 3.5 mm Rated current: 6 A Operating voltage: 300 VAC	ESD Suppressor WE-VE ULC 823 07 050 029 V_{DC} : 5 V C : 0.2 pF (1MHz) V_C : 17 V (30ns, contact) $I_{L,max}$: 0.1 μ A (V_{DC}) Size 0402	SMD Common Mode Choke WE-CNSW 744 232 090 $Z @ 100$ MHz: 90 Ω DCR: 0.30 Ω Rated current: 370 mA Size 1206
ESD Suppressor WE-VE 823 56 240 030 V_{DC} : 24 V C : 3 pF (1MHz) V_C : 200 V (1 A, 8/20 μ s) $I_{L,max}$: 1 μ A (V_{DC}) Size 0603	LAN Transformer 10/100 BaseT WE-LAN 749 010 012 Size 12.10 x 5.20 x 9.53 IL: 1-100 MHz / -1.1dB max RL: 1-80 MHz / -16 dB to -10 dB DCMRR: 30-100 MHz / -38 dB to -30 dB	LAN Transformer Gigabit WE-LAN 749 020 010 Size 17.30 x 6.50 x 16.00 IL: 1-100 MHz / -1.0 dB max RL: 1-100 MHz / -1 dB to -10 dB DCMRR: 30-100 MHz / -43 dB to -33 dB	RJ45 Modular Jack WR-COM 615 008 142 21 No. of Pins: 8 Rated current: 1.5 A Operating voltage: 120 VAC Shielded, Receptable THT	LAN RJ45 100 Base-T Transformer 749 921 1123 100 Base-T Tab down LED yellow - green Integrated magnetics	DVI Connector WR-COM 675 024 321 221 No. of Pins: 24 + 1 Rated current: 3 A Operating voltage: 40 V Shielded, Receptable, THT Digital	ESD Suppressor WE-VE femtoF 823 16 14 V_{DC} : 14 V C : 0.05 pF (1 MHz) V_C : 50 V (30ns, contact) $I_{L,max}$: 0.001 μ A Size 0603
ESD Suppressor WE-VE ULC 823 06 120 029 V_{DC} : 12 V C : 0.2 pF (1MHz) V_C : 30 V (30ns, contact) $I_{L,max}$: 0.1 μ A Size 0603	Chip Bead Ferrite WE-CBF 742 792 041 $Z @ 100$ MHz: 600 Ω DCR: 0.40 Ω Rated current: 500 mA Z max: 700 $\Omega @ 1600$ MHz Size 0805	Chip Bead Ferrite WE-CBF 742 792 60 $Z @ 100$ MHz: 40 Ω DCR: 0.15 Ω Rated current: 400 mA Z max: 60 $\Omega @ 1000$ MHz Size 0603	MiniDIN Connector WR-COM 631 004 112 021 No. of Pins: 4 Rated current: 1 A Operating voltage: 12 V Shielded, Receptable, THT	D-SUB Socket WR-DSUB 618 015 325 223 No. of Pins: 15 Rated current: 3 A Operating voltage: 125 VAC High Density Female	DVI Connector WR-COM 675 024 321 321 24 + 5 Rated current: 3 A Operating voltage: 40 V Shielded, Receptable, THT Analog & Digital	Evaluation Board for Chip Bead Ferrits and Common Mode Chokes EP-CBF-0805 EP-CBF-1206 EP-Stroko
ESD Suppressor WE-VE 823 56 120 100 V_{DC} : 5 V C : 100 pF (1MHz) V_C : 30 V (1 A, 8/20 μ s) $I_{L,max}$: 1 μ A (V_{DC}) Size 0603	Chip Bead Ferrite WE-CBF 742 792 094 $Z @ 100$ MHz: 2200 Ω DCR: 0.60 Ω Rated current: 200 mA Z max: 3000 $\Omega @ 80$ MHz Size 0805	D-SUB Connector 618 009 248 23 No. of Pins: 9 Rated current: 3 A Operating voltage: 250 VAC Male	D-SUB Socket WR-DSUB 618 009 211 821 No. of Pins: 9 Rated current: 3 A Operating voltage: 250 VAC Female	Terminal Block WR-TBL 691 102 710 003 No. of Pins: 3 AWG: 14-22 Pitch: 5 mm Rated current: 15 A Operating voltage: 300 VAC	Terminal Block WR-TBL 691 212 710 002 No. of Pins: 2 AWG: 12-22 Pitch: 5 mm Rated current: 10 A Operating voltage: 300 VAC	Ethernet Evaluation Board Evaluation Board for Ethernet (RJ45 / integrated connector) performance testing

Applications

- USB 1.0
- USB 1.1
- USB 2.0
- CAN
- Ethernet
- VGA
- RS232
- RS485
- DVI

Please check datasheets on www.we-online.com for specifications. Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions. © 2009

www.we-online.com