


PROPRIETARY INFORMATION:
 PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR
 USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY
 PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.

REVISION			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE, RFS. 27273	02/14/19	MK



GENERAL SPECIFICATIONS:

RATING: 20A / 120V AC
 CABLE TYPE / SIZE: SO, 12 AWG X 3C
 TEMPERATURE RATING: 60° C
 CONDUCTOR COLORS: BLACK / WHITE / GREEN
 CABLE JACKET COLOR: BLACK
 OVERALL LENGTH (L): 2000 ± 50 mm
 CABLE OUTER DIAMETER: 11.0 ± 0.5 mm
 END 'A' PLUG: NEMA 5-20P
 END 'B': SEE TABLE
 APPROVALS PLUG: UL, CSA or cUL
 APPROVALS CABLE: UL, CSA or cUL

PACKING:
 BULK PACK

NOTES:

1. CORD, PLUG AND CONNECTOR MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).



CONDUCTORS TERMINATION TABLE:

Wire	Color	ROJ ± 5 mm	R I J± 1 mm	Terminal
Line	Black	150mm	6 mm	Strip
Neutral	White	150mm	6 mm	Strip
Ground	Green	150mm	6 mm	Strip

RELEASED
 By N.Frost at 3:26 pm, Feb 14, 2019



DASH NO.	PART NO	REV.	DESCRIPTION	NOTES
TABULATION BLOCK				
INIT.BY: DR		DATE: 02/14/19	GlobTek, Inc. www.globtek.com 186 Veterans Dr. Northvale, NJ 07647 Tel. 201-784-1000 Fax 201.784.0111	
DRAWN: NF		DATE: 02/14/19	FSCN No.: G, CC, YL	SIZE: A
APRVD: MK		DATE: 02/14/19	SCALE: NONE	PART NO: 3201776F6000(R)
DWG TITLE: NORTH AMERICAN NON-DETACHABLE CORDSET				REV. A
SHEET 1 / 1				

Foot Note:
 Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applicable UL, CSA or EN Standards for proper installation instruction.

Limitation of Use:
 Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.

Contents of this document are subject to change without prior notice