



## Ordering Information

Model	Operating Temp. †	Processor	Cores	Hyper-Threading / Threads	CPU Clock / Turbo Speed	Graphics Core	Graphics Base Clock / Max Dynamic Speed	Memory	Cooling
VL-EPU-4462-EAP-08	-40° to +85°C	i3-6100U	2	Yes / 4	2.3 GHz / NA	HD 520	300 MHz / 1.0 GHz	8 GB	Heat plate
VL-EPU-4462-EBP-16	-40° to +85°C	i5-6300U	2	Yes / 4	2.4 GHz / 3.0 GHz	HD 520	300 MHz / 1.0 GHz	16 GB	Heat plate
VL-EPU-4462-ECP-16 *	-40° to +85°C	i7-6600U	2	Yes / 4	2.6 GHz / 3.4 GHz	HD 520	300 MHz / 1.05 GHz	16 GB	Heat plate
VL-EPU-4562-EBP-16	-40° to +85°C	i5-6442EQ	4	No / 4	1.9 GHz / 2.7 GHz	HD 530	350 MHz / 1.0 GHz	16 GB	Heat plate
VL-EPU-4562-ECP-16	-40° to +85°C	i7-6822EQ	4	Yes / 8	2.0 GHz / 2.8 GHz	HD 530	350 MHz / 1.0 GHz	16 GB	Heat plate
VL-EPU-4562-ECP-32	-40° to +85°C	i7-6822EQ	4	Yes / 8	2.0 GHz / 2.8 GHz	HD 530	350 MHz / 1.0 GHz	32 GB	Heat plate
VL-EPU-4462-SAP-04 *	0° to +60°C	i3-6100U	2	Yes / 4	2.3 GHz / NA	HD 520	300 MHz / 1.0 GHz	4 GB	Heat plate
VL-EPU-4462-SAP-08	0° to +60°C	i3-6100U	2	Yes / 4	2.3 GHz / NA	HD 520	300 MHz / 1.0 GHz	8 GB	Heat plate
VL-EPU-4462-SBP-16	0° to +60°C	i5-6300U	2	Yes / 4	2.4 GHz / 3.0 GHz	HD 520	300 MHz / 1.0 GHz	16 GB	Heat plate
VL-EPU-4462-SCP-16 *	0° to +60°C	i7-6600U	2	Yes / 4	2.6 GHz / 3.4 GHz	HD 520	300 MHz / 1.05 GHz	16 GB	Heat plate
VL-EPU-4562-SBP-16	0° to +60°C	i5-6442EQ	4	No / 4	1.9 GHz / 2.7 GHz	HD 530	350 MHz / 1.0 GHz	16 GB	Heat plate
VL-EPU-4562-SCP-16	0° to +60°C	i7-6822EQ	4	Yes / 8	2.0 GHz / 2.8 GHz	HD 530	350 MHz / 1.0 GHz	16 GB	Heat plate
VL-EPU-4562-SCP-32	0° to +60°C	i7-6822EQ	4	Yes / 8	2.0 GHz / 2.8 GHz	HD 530	350 MHz / 1.0 GHz	32 GB	Heat plate

\* Special Order Product. Contact VersaLogic Sales for minimum order quantities and lead time.

† Derate -1.1°C per 305m (1,000 ft.) above 2,300m (7,500 ft.).

## Export Information

Description	Value
ECCN:	5A992.c
SCHEDULE B:	8471.60.7000

## Ordering Information

Model	Operating Temp.†	Processor	Cores	CPU Clock / Turbo Speed	Graphics Core	Graphics Base Clock / Max Dynamic Speed	Memory	Cooling
VL-EPU-4460-SAP-04 *	0° to +60°C	i3-6100U	2	2.3 GHz / NA	HD 520	300 MHz / 1.0 GHz	4 GB	Heat plate
VL-EPU-4460-SAP-08	0° to +60°C	i3-6100U	2	2.3 GHz / NA	HD 520	300 MHz / 1.0 GHz	8 GB	Heat plate
VL-EPU-4460-SBP-16	0° to +60°C	i5-6300U	2	2.4 / 3.0 GHz	HD 520	300 MHz / 1.0 GHz	16 GB	Heat plate
VL-EPU-4460-SCP-16	0° to +60°C	i7-6600U	2	2.6 / 3.4 GHz	HD 520	300 MHz / 1.05 GHz	16 GB	Heat plate
VL-EPU-4460-EAP-08	-40° to +85°C	i3-6100U	2	2.3 GHz / NA	HD 520	300 MHz / 1.0 GHz	8 GB	Heat plate
VL-EPU-4460-EBP-16	-40° to +85°C	i5-6300U	2	2.4 / 3.0 GHz	HD 520	300 MHz / 1.0 GHz	16 GB	Heat plate
VL-EPU-4460-ECP-16	-40° to +85°C	i7-6600U	2	2.6 / 3.4 GHz	HD 520	300 MHz / 1.05 GHz	16 GB	Heat plate
VL-EPU-4460-ECP-32 *	-40° to +85°C	i7-6600U	2	2.6 / 3.4 GHz	HD 520	300 MHz / 1.05 GHz	32 GB	Heat plate

\* Special Order Product. Contact VersaLogic Sales for minimum order quantities and lead time.

## Export Information

Description	Value
ECCN:	5A992.c
SCHEDULE B:	8471.60.7000