




GENERAL INFORMATION

TYPE	CompactFlash™
INTERFACE	PCMCIA/IDE
DATA TRANSFER MODE	UDMA0-6, MDMA0-4 & PIO0-6
CONNECTOR	CFC Type I
OUTLINE DIMENSIONS	36.4 x 42.8 x 3.3 mm
SERIES	CFE9D
CONTROLLER TYPE 	TDK GBDriver RA9
FLASH TYPE	SLC
DENSITY RANGE	128 MB - 32 GB
DATA RETENTION	10 years @ life begin-10% 1 year @ life end
ENDURANCE ENTERPRISE WL	128 MB ~ 4 GB: 50,000 P/E Cycles 8 GB ~ 32 GB: 100,000 P/E Cycles *Flash Block Level

TEMPERATURE

OPERATING TEMPERATURE	Commercial: 0°C to +70°C Industrial: -40°C to +85°C
STORAGE TEMPERATURE	Commercial: -25°C to +85°C Industrial: -40°C to +85°C

PERFORMANCE

Read (max.)	50 MByte/sec
Write (max.)	35 MByte/sec

ROBUSTNESS

MTBF	≥ 2,500,000 hours
SHOCK	1000G, 0.5ms
VIBRATION	15G, 10-500Hz
HUMIDITY	0 to 90 % RH (No condensation)

ELECTRICAL DATA

VOLTAGE	3.3 V ± 5 % / 5 V ± 10 %
POWER CONSUMPTION (*RT)	- Single mode UDMA Read Write: 145mA @ 3.3V / 85mA @ 5.0V - 2ch mode UDMA Read Write: 220mA @ 3.3V / 130mA @ 5.0V - Stand-by: 10mA @ 3.3V / 10mA @ 5.0V

FEATURE LIST

FEATURES & TOOLS	- In-House Designed Controller (HW/FW) - DRAM-less Design - Power Fail Data Safety - Power Back-up Circuit - Global static wear leveling - SMART - TRIM
PART NUMBER	CFE9DxxxxTxxxB00EAA0