# 1438759-1 ✓ ACTIVE

## Multilock Connector System

TE Internal #: 1438759-1

Wire-to-Wire, 22 Position, .098 in [2.5 mm] Centerline, White, Signal, Cable Mount (Free-Hanging), Multilock Connector System

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > MULTILOCK, CONNECTOR HOUSING



Mating Tab Width: 1 mm [ .039 in ]
Connector System: Wire-to-Wire

Number of Positions: 22

Centerline (Pitch): 2.5 mm [ .098 in ]

Sealable: No

### All MULTILOCK, CONNECTOR HOUSING (567)

## **Features**

## **Product Type Features**

Connector Shape	Rectangular
Connector System	Wire-to-Wire
Sealable	No
Hybrid Connector	Yes
Configuration Features	
Number of Positions	22
Number of Rows	2
Body Features	
Primary Product Color	White
Connector & Keying Code	В
Contact Features	

## Mechanical Attachment

Mating Tab Width

Contact Size

Terminal Position Assurance	No
Strain Relief	Without
Mating Alignment Type	Keyed

1mm

1 mm[.039 in]



Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PBT
Centerline (Pitch)	2.5 mm[.098 in]
Dimensions	
Connector Height	25.55 mm[1.006 in]
Product Width	19.75 mm[.778 in]
Product Length	38 mm[1.496 in]
Usage Conditions	
Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C[158 °F][167 °F][176 °F][185 °F][194 °F] [212 °F][221 °F]
Operating Temperature Range	-30 - 105 °C[-22 - 221 °F]
Operation/Application	
Circuit Application	Signal
Packaging Features	
Packaging Quantity	45
Packaging Method	Package
Other	
Connector Position Assurance Capable	No

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free



### Solder Process Capability

Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts







# Also in the Series | Multilock Connector System







Automotive Connector EMC Shielding (1)



Automotive Connector Locks & Position Assurance(2)



Automotive Housings(603)



Automotive Seals & Cavity Plugs(2)



Automotive Terminals(141)



Insertion & Extraction Tools(6)



Other Automotive Connector Accessories(14)






## Customers Also Bought

















## **Documents**

## **Product Drawings**

22WAY HYBRID .040/2.8 PLUG ASSY KEY 'B'

English

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1438759-1\_E.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1438759-1\_E.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1438759-1\_E.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Wire-to-Wire, 22 Position, .098 in [2.5 mm] Centerline, White, Signal, Cable Mount (Free-Hanging), Multilock Connector System



Datasheets & Catalog Pages

MULTILOCK Connector System

English

**Product Specifications** 

**Application Specification** 

English

**Instruction Sheets** 

Instruction Sheet (U.S.)

English