

APPLICATOR PARTS LIST				TYPE LENGTHWISE <i>RING AMPLIFIER STUD RETAINING</i>			AMP INCORPORATED HARRISBURG, PENNA.					
NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	CRIMPING DATA			TERMINALS	
1	WIRE CRIMPER	1	452422-1	42				TO APPLY TERMINAL			505071	
2	INL. CRIMPER			43				WIRE SIZE	CRIMP HEIGHT			
3	ANVIL	1	473405-9	44				20 AWG	.054			
4	ANVIL SPACER			45				18 "	.057			
5	SHEAR BLADE	1	245233-5	46				16 "	.062			
6	REAR SHEAR PLATE	1	385013-4	47				19+20	.061			
7	SHEAR BLADE SPACER	2	373072	48				18 STRIP 20 MAG	.062			
8	FRONT SHEAR PLATE	1	470057-3	49				CRIMP	SIZE	TYPE	FEED	
9	REAR ANVIL SPACER PLT.	1	386149	50				WIRE	.110	F		
10	FRONT ANVIL SPACER PLT.	1	385528	51				INSUL.			1.300	
11	TOOL SPACER	2	371955	52				SLEEVED				
12	CRIMP SPACER			53	HOLD DOWN (BLADE M.)	1	811065-1					
13	FRONT STRIP GUIDE	1	379034-1	54				WIRE RANGE				
14	REAR STRIP GUIDE	1	379034-2	55				MAGNET WIRE 20-16				
				56				EXPLODED VIEW				
15	RAM	1	471167	57				A-6000 A-6000-1				
16	TOOL HOLDER	1	376046	58				REMARKS:				
17	ADJ. CRIMP MOUNT			59								
18	ADJ. BLOCK			60								
19	APPLICATOR MOUNT	1	570656	61								
20	BASE PLATE			62	WIPPER HEX 1/2 T-3/8	1	22304-5					
21	BASE BLOCK			63	WIPPER FLAW KANTREL	1	23054-1					
22	STRIP GUIDE PLATE			64	AIR FEED ASSY (2")	1	690021					
23	ANVIL HOLDER	1	370526	65	TENSION ADJ. PLATE	1	574999					
24	AUX. ANVIL HOLDER	1	377515	MISCELLANEOUS								
25	STRIPPER	1	810072-1	66	LUBRICATOR ASSY	1	465184-2					
26	STRIPPER MOUNT	1	386231	67	TERMINAL LUBRICANT	REAR	52281-2					
27	RETAINER PLATE	1	372251	68								
28	STRIPPER MOUNT BRACKET			69								
29	STRIPPER BUSHING			70								
30	STOCK DRAG	1	375381	71								
31	STOCK DRAG HANDLE			72								
32	STOCK DRAG STUD	2	354045-1	REV.	REVISION RECORD	DATE	BY	ECN	THIS APPLICATOR IS TO BE USED ON			
33	STOCK DRAG SPRING	2	1-25047-1	A	REV PER ECN R-5734	6/1/84	DBK	-	AMP-O-LECTRIC 1-471273-2			
34	STOCK DRAG ADJ. SCREW	2	378997	B	EC-A-272490	5-78	DBK	-	AMP-O-MATIC AIR FEED			
35	FEED FINGER HOLDER			C	ECN A-395892	9-92	DBK	-	ALIGN. GA. 679597-1			
36	FEED FINGER	1	375093						SERIAL NO.	DATE SHIPPED	DESIGNED	
37	FEED FINGER TIP								CUSTOMER NAME AND ADDRESS			
38	FEED FINGER SPACER								CHK'D.			
39	BASE CASTING	1	570238						APPROVED			
40	GUARD	1	375647						12-77			
41	SPACER, GUARD	1	375570						APPLICATOR NUMBER	REV. C	566259-1	SHEET 1 OF 1

FOR HARDWARE SEE 5-687500-6