TE Internal #: 3-1761465-1

PCI & PCI Express Connectors, Board-to-Board, 36 Position, .039 in

[1 mm] Centerline, Right Angle, Black, Height .37 in [9.4 mm]


View on TE.com >



Connectors > PCB Connectors > Card Edge Connectors > PCI & PCI Express Connectors











Connector System: Board-to-Board

Number of Positions: 36

Centerline (Pitch): 1 mm [.039 in]

Termination Post & Tail Length: 3.1 mm [.122 in]

Contact Mating Area Plating Material Thickness: [15 µin]

Features

Product Type Features

Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of PCB Mount Retention Features	2
Number of Positions	36
PCB Mount Orientation	Right Angle
Ejector	Without
Electrical Characteristics	
Operating Voltage	50 VAC
Body Features	

Contact Features

Product Weight

Primary Product Color

Contact Mating Area Plating Material Gold

21.302 g

Black



Contact Underplating Material PCB Contact Termination Area Plating Material Tin Contact Base Material Phosphor Bronze 15 µin Contact Current Rating (Max) 1.1 A Termination Features Termination Method to Printed Circuit Board Tormination Post & Tail Length 3.1 mm, 1722 inj Mechanical Attachment Connector Mounting Type Board Mount Housing Features Housing Material High Temperature Nylon Centerline (Pitch) 1 mm [039 in] Dimensions PCB Thickness (Accepted) 1.57 mm [062 in] Connector Height Quantity Connector Width 19.6 mm [772 in] Usage Conditions Operating Temperature Range 40 85 °C 40 - 185 °F Operation/Application Circuit Application Signal Industry Standards Bus Type PCI Express		
Contact Base Material Phosphor Bronze 15 µin Contact Current Rating (Max) 1.1 A Termination Features Termination Method to Printed Circuit Board Through Hole - Solder Termination Post & Tail Length 3.1 mm[.122 in] Mechanical Attachment Connector Mounting Type Board Mount Housing Features Housing Material High Temperature Nylon Centerline (Pitch) 1 mm[.039 in] Dimensions PCB Thickness (Accepted) 1.57 mm[.062 in] Connector Height 9.4 mm[.37 in] Connector Width 19.6 mm[.772 in] Usage Conditions Operating Temperature Range 40 – 85 °C[.40 – 185 °F] Operation/Application Gircuit Application Industry Standards Bus Type PCI Express	Contact Underplating Material	Nickel
Contact Current Rating (Max) 1.1 A Termination Features Termination Method to Printed Circuit Board Through Hole Solder Termination Post & Tail Length 3.1 mml. 122 in] Mechanical Attachment Connector Mounting Type Board Mount Housing Features Housing Material High Temperature Nylon Centerline (Pitch) 1 mml. 039 in] Dimensions PCB Thickness (Accepted) 1.57 mml. 062 in] Connector Height 9.4 mml. 37 in] Connector Width 19.6 mml. 772 in] Usage Conditions Operating Temperature Range 40 - 85 °C[40 - 185 °F] Operation/Application Circuit Application Signal Industry Standards Bus Type PCI Express	PCB Contact Termination Area Plating Mater	al Tin
Contact Current Rating (Max) Termination Features Termination Method to Printed Circuit Board Termination Post & Tail Length 3.1 mm[.122 in] Mechanical Attachment Connector Mounting Type Board Mount Housing Features Housing Material Centerline (Pitch) 1 mm[.039 in] Dimensions PCB Thickness (Accepted) 1.57 mm[.062 in] Connector Width 9.4 mm[.37 in] Connector Width 19.6 mm[.772 in] Usage Conditions Operating Temperature Range 40 – 85 °C[40 – 185 °F] Operation/Application Circuit Application Signal Industry Standards Bus Type PCI Express	Contact Base Material	Phosphor Bronze
Termination Features Termination Method to Printed Circuit Board Through Hole - Solder Termination Post & Tail Length 3.1 mm[.122 in] Mechanical Attachment Connector Mounting Type Board Mount Housing Features Housing Material High Temperature Nylon Centerline (Pitch) 1 mm[.039 in] Dimensions PCB Thickness (Accepted) 1.57 mm[.062 in] Connector Height 9.4 mm[.37 in] Connector Width 19.6 mm[.772 in] Usage Conditions Operating Temperature Range 40 85 °C[40 – 185 °F] Operation/Application Circuit Application Signal Industry Standards Bus Type PCI Express		15 μin
Termination Method to Printed Circuit Board Termination Post & Tail Length 3.1 mm[.122 in] Mechanical Attachment Connector Mounting Type Board Mount Housing Features Housing Material Centerline (Pitch) Dimensions PCB Thickness (Accepted) Connector Height Connector Width 19.6 mm[.772 in] Usage Conditions Operating Temperature Range -40 - 85 °C[-40 - 185 °F] Operation/Application Circuit Application Industry Standards Bus Type PCI Express	Contact Current Rating (Max)	1.1 A
Termination Post & Tail Length Mechanical Attachment Connector Mounting Type Board Mount Housing Features Housing Material Centerline (Pitch) Dimensions PCB Thickness (Accepted) Connector Height Connector Width 19.6 mm[.772 in] Usage Conditions Operating Temperature Range Circuit Application Industry Standards Bus Type PCI Express	Termination Features	
Mechanical Attachment Connector Mounting Type Board Mount Housing Features Housing Material High Temperature Nylon Centerline (Pitch) 1 mm[.039 in] Dimensions PCB Thickness (Accepted) 1.57 mm[.062 in] Connector Height 9.4 mm[.37 in] Connector Width 19.6 mm[.772 in] Usage Conditions Operating Temperature Range -40 – 85 °C[-40 – 185 °F] Operation/Application Circuit Application Signal Industry Standards Bus Type PCI Express	Termination Method to Printed Circuit Board	Through Hole - Solder
Connector Mounting Type Housing Features Housing Material Centerline (Pitch) Dimensions PCB Thickness (Accepted) Connector Height Connector Width Usage Conditions Operating Temperature Range Circuit Application Circuit Application Industry Standards Bus Type Board Mount Bloard Mount Board Mount Board Mount Board Mount Advantable Seatures Board Mount High Temperature Nylon 1 mm[.039 in] 1 mm[.039 in] 1 mm[.062 in] 2 nm [.062 in] 1 y.4 mm[.37 in] 2 nm [.772 in] Vage Conditions Signal	Termination Post & Tail Length	3.1 mm[.122 in]
Housing Features Housing Material High Temperature Nylon Centerline (Pitch) 1 mm[.039 in] Dimensions PCB Thickness (Accepted) 1.57 mm[.062 in] Connector Height 9.4 mm[.37 in] Connector Width 19.6 mm[.772 in] Usage Conditions Operating Temperature Range -40 – 85 °C[-40 – 185 °F] Operation/Application Circuit Application Signal Industry Standards Bus Type PCI Express	Mechanical Attachment	
Housing Material High Temperature Nylon Centerline (Pitch) 1 mm[.039 in] Dimensions PCB Thickness (Accepted) 1.57 mm[.062 in] Connector Height 9.4 mm[.37 in] Connector Width 19.6 mm[.772 in] Usage Conditions Operating Temperature Range -40 – 85 °C[-40 – 185 °F] Operation/Application Circuit Application Signal Industry Standards Bus Type PCI Express	Connector Mounting Type	Board Mount
Centerline (Pitch) Dimensions PCB Thickness (Accepted) Connector Height Connector Width 19.6 mm[.772 in] Usage Conditions Operating Temperature Range Circuit Application Circuit Application Signal Industry Standards Bus Type PCI Express	Housing Features	
Dimensions PCB Thickness (Accepted) 1.57 mm[.062 in] Connector Height 9.4 mm[.37 in] Connector Width 19.6 mm[.772 in] Usage Conditions Operating Temperature Range -40 – 85 °C[-40 – 185 °F] Operation/Application Circuit Application Signal Industry Standards Bus Type PCI Express	Housing Material	High Temperature Nylon
PCB Thickness (Accepted) Connector Height 9.4 mm[.37 in] Connector Width 19.6 mm[.772 in] Usage Conditions Operating Temperature Range -40 - 85 °C[-40 - 185 °F] Operation/Application Circuit Application Signal Industry Standards Bus Type PCI Express	Centerline (Pitch)	1 mm[.039 in]
Connector Height 9.4 mm[.37 in] Connector Width 19.6 mm[.772 in] Usage Conditions Operating Temperature Range -40 – 85 °C[-40 – 185 °F] Operation/Application Circuit Application Signal Industry Standards Bus Type PCI Express	Dimensions	
Connector Width Usage Conditions Operating Temperature Range -40 – 85 °C[-40 – 185 °F] Operation/Application Circuit Application Signal Industry Standards Bus Type PCI Express	PCB Thickness (Accepted)	1.57 mm[.062 in]
Usage Conditions Operating Temperature Range -40 – 85 °C[-40 – 185 °F] Operation/Application Circuit Application Signal Industry Standards Bus Type PCI Express	Connector Height	9.4 mm[.37 in]
Operating Temperature Range -40 – 85 °C[-40 – 185 °F] Operation/Application Circuit Application Signal Industry Standards Bus Type PCI Express	Connector Width	19.6 mm[.772 in]
Operation/Application Circuit Application Industry Standards Bus Type PCI Express	Jsage Conditions	
Circuit Application Industry Standards Bus Type PCI Express	Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
Industry Standards Bus Type PCI Express	Operation/Application	
Bus Type PCI Express	Circuit Application	Signal
	ndustry Standards	
Packaging Features	Bus Type	PCI Express
i ackaging i eatures	Packaging Features	
Packaging Quantity 100		100
Packaging Method Box & Tray, Tray		Box & Tray, Tray

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant



China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Customers Also Bought





















Documents

Product Drawings

PCI Express RA assy 5.8mm slot 2.3mm pc

English

BLUE

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_3-1761465-1_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_3-1761465-1_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_3-1761465-1_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

4-1773442-7 Card Edge Connector for PCI Express Applications

English

Product Specifications

Product Specification

English

Product Environmental Compliance

Product Compliance Document

PCI & PCI Express Connectors, Board-to-Board, 36 Position, .039 in [1 mm] Centerline, Right Angle, Black, Height .37 in [9.4 mm]



English

Product Compliance Document

English