

LB SCHRAUBE MIT ISOL. GY - Bridge screw



5029112

<https://www.phoenixcontact.com/us/products/5029112>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Bridge screw, M3, length: 30 mm, color: gray



Commercial data

Item number	5029112
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BE19
Product key	BE1Z2X
GTIN	4017918287122
Weight per piece (including packing)	1.399 g
Weight per piece (excluding packing)	1.366 g
Customs tariff number	74153300
Country of origin	PL

5029112

<https://www.phoenixcontact.com/us/products/5029112>

Technical data

Product properties

Product type	Mounting material
--------------	-------------------

Dimensions

Width	4.75 mm
Height	30.3 mm
Length	30.3 mm

Material specifications

Color	gray
Material	Brass, nickel-plated
Insulating material	PA

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

LB SCHRAUBE MIT ISOL. GY - Bridge screw



5029112

<https://www.phoenixcontact.com/us/products/5029112>

Classifications

ECLASS

ECLASS-11.0	27141140
ECLASS-12.0	27141140
ECLASS-13.0	27250303

ETIM

ETIM 8.0	EC000489
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

LB SCHRAUBE MIT ISOL. GY - Bridge screw



5029112

<https://www.phoenixcontact.com/us/products/5029112>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com