

- UFBK 2-PE- 12AC-ST - 2792248


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Protective plug for base element UFBK 2-PE-12 AC, protection for conductor pairs in floating circuits, nominal voltage: 12 V AC, color: Black

Product description

Two conductor protective plug in floating signal circuits. The function of the protective device can be checked with a separate testing device and the result can be documented via a printer.

Key commercial data

Packing unit	1 pc
GTIN	 4 017918 072629
Weight per Piece (excluding packing)	80.55 GRM
Custom tariff number	85363010
Country of origin	Germany

Technical data

Dimensions

Horizontal pitch	1 Div.
------------------	--------

Ambient conditions

Ambient temperature (operation)	-40 °C ... 60 °C
Degree of protection	IP20

General

Housing material	PA
Inflammability class according to UL 94	V2
Arrester can be tested with TT-Tester from software version:	From SW rev. 6.00
Arrester can be tested with CHECKMASTER from software version:	From SW rev. 1.00

Protective circuit

Nominal voltage U_N	12 V AC
Nominal current I_N	2 A
Nominal discharge current I_n (8/20) μ s (Core-Core)	10 kA
Output voltage limitation at 1 kV/ μ s (Core-Core) spike	\leq 23.4 V
Output voltage limitation at 1 kV/ μ s (Core-Earth) spike	\leq 650 V
Response time t_A (Core-Core)	\leq 1 ns

- UFBK 2-PE- 12AC-ST - 2792248

Technical data

Protective circuit

Response time tA (Core-Earth)	100 ns
Inductivity in series	80 µH (Path 1-3/2-4)
Resistance in series	100 mΩ (Path 1-3/2-4)

Classifications

eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130807

ETIM

ETIM 2.0	EC000943
ETIM 3.0	EC000943
ETIM 4.0	EC000943
ETIM 5.0	EC000943

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 13.2	39121620