


AE-B48-16SP2



DIP40/BGA48 specialized adapter for FLASH memory.
Device package dimensions: 8.15 x 6.15 x 1.0 mm, 0.8 mm pitch.

Click the programmer model below to get an appropriate list of the devices supported by the adapter:

- [ChipProg+](#)
- [ChipProg-40](#)

Adapter Connection Table:

DIP-40	BGA-48	74HC573	C1, 150pF	C2, 0.1uF
	D6	16		
	C6	17		
	A6	18		
	B6	19		
12	D5			
11	C5			
10	A5			
9	B5			
	D4	12		
13	D3			
15	A4			
14	B4			
17	C4			
18	B3			
16	A3			
	C3	13		
	B2	14		
8	A2	9		
7	C2	8		
6	D2	7		

5	B1	6		
4	A1	5		
3	C1	4		
2	D1	3		
1	E1	2		
37	F1			
20	H1	1		
38	G1			
21	E2			
29	F2			
22	H2			
30	G2			
23	E3			
31	F3			
24	H3			
32	G3			
40	G4	20		1
25	H4			
33	F4			
26	E4			
34	G5			
27	H5			
35	F5			
28	E5			
36	G6			
20	H6	10	1	2
39	F6			
	E6	15		
19		11	2	