Data sheet | Item number: 890-644

Lockout cap; 4-pole; for cutouts; Plastic; black

www.wago.com/890-644



Color:

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/890-644



Item description

Cover WINSTA® MINI 4-pole

The cover from the WINSTA® MINI product line is the best solution for reliable installation. You can rely on the level of quality of WINSTA® components from WAGO for your electrical installation accessories too. Especially where space is tight, our smallest pluggable connection system, WINSTA® MINI, conveniently displays its advantages. It is very compact, and, with Push-in CAGE CLAMP® spring pressure connection technology, it additionally saves time, since the installation is low-maintenance and can be performed without screw connections.

Push-in CAGE CLAMP® spring pressure connection technology – pluggable installation instead of laborious screw connections!

The WINSTA® Pluggable Connection System allows pluggable electrical installation. This significantly reduces the need for servicing and lowers costs. Choose durability and quality – the WINSTA® MINI accessory with protection against mismating from WAGO makes the electrical installation of electrical components noticeably easier.

- compact design for conductors with a cross-section up to 1.5 mm²
- quick replacement of defective units during ongoing operation

Data

Connection data

Connection 1

Pole number 4

Mechanical Data

Mounting type	Snap-in flange
Suitable	for cutout

Material Data

Note (material data)

Information on material specifications can be found here

Color black

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

Data sheet | Item number: 890-644

www.wago.com/890-644



Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.045 MJ
Weight	1.5 g

Environmental requirements

Processing temperature	-5 +40 °C
Continuous operating temperature	-35 +85 ℃
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

Product Group	20 (Winsta)
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 8.0	EC002863
ETIM 7.0	EC002863
PU (SPU)	100 pcs
Packaging type	box
Country of origin	DE
GTIN	4050821684312
Customs tariff number	39269097900

Environmental Product Compliance

RoHS Compliance Status	Compliant,No Exemption
------------------------	------------------------

Downloads

Documentation

Bid Text

890-644 doc - Datei	2019 年3月5日	doc 23.6 kB	Download
890-644 X81 - Datei	2019 年3月5日	xml 3.0 kB	Download

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO GmbH & Co. KG

Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

Data sheet | Item number: 890-644

www.wago.com/890-644



CAD/CAE-Data

CAE data

WSCAD Universe 890-644 URL Download

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 890-644 URL Download

Lockout cap; 4-pole; for cutouts; Plastic; black

Installation Notes

Product family

WINSTA® MINI

Show all products from the family

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.