

Recommended PCB Layout (Top View)

**Specifications** 

Materials & Plating

Plastic Housing: LCP, Blue, UL94V-0 Contact Terminal: Copper Alloy,T=0.20mm

Metallic Shell: SUS201,T=0.30mm

## Plating:

Contact:

Contact Area: Gold Flash Solder Tails: 100u" min. Tin Underplating: 50u" min. Nickel Shell: 50u" min. Nickel Plating Overall

Electrical:

Voltage Rating: 30V

Current Rating: 0.25A (Signal Pins)

3.0A (Power Pins)


Operating Temperature: -40°C to +85°C


Contact Resistance:


30 mΩ max. (Power Pins) 50 mΩ max. (Signal Pins)

Insulation Resistance: 100  $M\Omega$  min.

Dielectric Withstand Voltage: 100V R.M.S.







Section A-A

## Ordering Grid



A2

08/12/20

Date

GF = Gold Flash B = Tray (100 per tray)


## Mechanical:

Mating Force: 35N max.

Unmating Force: 10N min. Initial

8N. min. Final

Durability: 20000 Cycles



4.00

7.00

8.00 15.30±0.15 2.00

Pin No.	Signal
1	VBUS
2	D-
3	D+
4	GND
5	STDA_SSRX-
6	STDA_SSRX+
7	GND_DRAIN
8	STDA_SSTX-
9	STDA_SSTX+

1.38

Part Number Product Description USB1086 USB 3.0 Receptacle, Type A, Through Hole, Drawing Date Vertical, Top Mount 06th January 2020 Tolerances (Except as Noted) Length Angle This drawing is confidential and copyright of Global Connector RoHS COMPLIANT 2011/65/EU Drawing Detail Technology, Ltd (GCT).
This drawing must not be copied X.X ± 0.35 X.° ± 3.0°  $\oplus \Box$ Revision



X.X° ± 1.5°

X.XX ± 0.25

Deca-BDE C

or disclosed without written

Not to Drawn By

