

# 400G Multimode 50/125 OM4 Plenum Fiber Optic Cable, 16F MTP/MPO-APC to (x2) 12F MTP/MPO-UPC (F/F), Magenta, 3 m

MODEL NUMBER: N846D-03M-16DMG











400 GbE Ethernet cable supports high bandwidths necessary for next-generation cloud services, hyperscale data centers and telecom carriers.

### **Features**

**400 GbE Cable Supports Higher Bandwidths Needed for Next-Gen Data and Voice Networking** As the amount of traffic in data networks grows, so does the need for next-generation devices and fiber cables to support much higher bandwidths in cloud services, hyperscale data centers, telecom applications and equipment OEM companies. This multimode 50/125 OM4 cable is an ideal choice for 400G Ethernet applications up to 100 meters (at 850 nm). It has documented insertion loss and back reflection testing on every connector and attenuation loss that meets or exceeds current standards.

16-Fiber and 12-Fiber MTP/MPO Connectors Designed for the Latest QSFP-DD Transceivers
The MPO connectors have a wide parallel optical interface for use with the latest 400G QSFP-DD
transceivers, making this cable an excellent solution for your high-density network application. The
connectors are the same size as standard SC connectors, but 12 times denser, allowing vertical stacking
in switches or patch panels where space is at a premium. Pull tabs make the cable easy to install or
remove with one hand.

## Magenta Jacket Helps Avoid Misidentification That Can Cause Costly Downtime

The OM4-rated cable has a magenta jacket, which is easy to identify quickly in a crowded patch panel or switch and helps prevent the cable from becoming accidentally disconnected. The three-millimeter ruggedized plenum-rated jacket has low smoke and flame characteristics, making it suitable for premise applications in ceilings, walls and ducts.

# **Specifications**

OVERVIEW	
UPC Code	037332258328
Technology	Multimode

## **Highlights**

- OM4-rated cable recommended for 400 Gb speeds up to 100 m (@ 850 nm)
- MTP/MPO 16- and dual 12-fiber ends designed for next-gen 400G QSFP-DD transceivers
- Connectors tested for low insertion loss and back reflection to ensure top performance
- Plenum rated for horizontal premise applications in air ducts and drop ceilings
- Magenta jacket allows fast, easy identification in a crowded switch or patch panel

#### **Applications**

- Connect 400G fiber Ethernet networks in your cloud service, hyperscale data center or telecom application
- Connect 400G Cisco, Arista, Juniper and other network switches through air ducts and drop ceilings

## **Package Includes**

N846D-03M-16DMG 400G Multimode 50/125 OM4 Fiber Optic Cable, Magenta, 3 m



Optical Mode	OM4	
PUNCIONAL		
PHYSICAL Ochlar Joseph of Ochlar	Manage	
Cable Jacket Color	Magenta	
Connector Color	Green; Black; Aqua	
Cable Jacket Material	PVC	
Cable Jacket Rating	OFNP	
Clad Diameter (microns)	125	
Core Diameter (microns)	50	
Primary Coating Diameter (microns)	245	
Number of Fibers	16	
Cable Length (ft.)	9.8	
Cable Length (m)	2.99	
Cable Length (in.)	118.1	
Minimum Bend Radius	20 mm (Dynamic); 10 mm (Static)	
Fiber Cable Length	3M (9.8 ft)	
ENVIRONMENTAL		
Operating Temperature Range	-4° to 140°F (-20° to 60°C)	
Storage Temperature Range	-4° to 140°F (-20° to 60°C)	
Operating Humidity Range	5% to 85% RH, Non-Condensing	
Storage Humidity Range	35% to 65% RH, Non-Condensing	
COMMUNICATIONS		
Network Compatibility	400 Gbps	
Transmission Distance	100M @ 850NM Wavelength	
Attenuation @ 850NM	3.0 dB/km	
Insertion Loss	16F: 0.60 dB; 24F: 0.35 dB	
CONNECTIONS		
Side A - Connector 1	16-STRAND MTP/MPO (FEMALE)	
Side B - Connector 1	(2) 12-STRAND MTP/MPO (FEMALE)	
Endface Polish	APC; UPC	
FEATURES & SPECIFICATIONS		
Push/Pull Tabs	No	
Breakout	No	



Trunk	No	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; REACH	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.