

Green Laser Module

1. Specification:

- | | |
|-------------------------------------|---|
| 1-1 Wavelength | 532nm |
| 1-2 Output power | 5mw(Laser spot)
(Measure under the temperature 25°C±3°C) |
| 1-3 Specs. Parameter | Fixed focus, dot shape facula, (facula pattern: TEMOO)
continuous output |
| 1-4 Standard Dimension | : φ12×66mm |
| 1-5 Beam Dimension | 6 Meter distance Output Laser spot 18mm ±2.0mm |
| 1-6 Input Power Source | DC3.2V |
| 1-7 Consumption Current | Less than 300mA |
| 1-8 Body | Brass |
| 1-9 Life Time | More than 5000 hours |
| 1-10 Beam of Light Emanative Angle: | 1.2mrad |
| 1-11 Work material : | Nd:YVO4+KTP |

2. Environment Condition:

- | | |
|--|--|
| 2-1 Storage Temperature and Humidity | -25°C~70°C / 93~95 Rh
(Storage in 3 weeks) |
| 2-2 Operating Temperature and Humidity | 0°C~40°C / 20~80 Rh
(No Condense) |

3. Reliability test:

- | | |
|-----------------------|--------------------|
| 3-1 vibration test: | depend on customer |
| 3-2 voltage test: | 2.8 to 3.2V |
| 3-3 temperature test: | 0°C to 50°C |