



FF0116BBCAEA01-WL



SINGLE POLE SOLDER LUG

Base Switch	Pole & Throw	Plunger Position		Connected Terminals		Throw & Switch Schematics
		Normal	Down	Normal	Down	
FF0116BBCAEA01	SPST	ON	OFF	11-12	OPEN	SPST NC

PANEL CUTOUT



Wiring			Wire Specifications	
Number of Wires	Terminal 11	Terminal 12	UL1007/UL1569 PVC	Temperature: +80°C and +105°C (+176°F and +221°F)
2	White	Brown	Voltage: 300V	
			22 AWG Stranded	Stripped Wire Ends .142" (3.6mm)

Base Switch Specifications

Electrical Capacity

Resistive Load: 0.5A @ 24V DC

Other Ratings

- Rated Insulation Voltage: 36V DC
- Impulse Withstand Voltage: 2.5kV
- Contact Resistance: 50 milliohms maximum
- Insulation Resistance: 100 megohms minimum @ 500V DC
- Mechanical Life: 100,000 operations minimum
- Electrical Life: 100,000 operations minimum
- Operating Force: Push to lock 10.8N; Pull to reset 8.5N; Turn to reset 0.13N·m
- Minimum Direct Operating Force: 15N
- Short Circuit Protection: gG10A
- Conditional Short Circuit Current: 1000A
- Minimum Positive Opening Travel: .118" (3.0mm)
- Total Travel: .177" (4.5mm)
- Operation Frequency: 10 times per minute
- Overvoltage Category: II

Materials & Finishes

- Actuator: Glass fiber reinforced polyester (PBT)
- Housing: Glass fiber reinforced polyamide
- Movable Contacts: Silver alloy copper with gold plating
- Stationary Contacts: Silver alloy copper with gold plating
- Terminals: Brass with tin plating

Environmental Data

- Operating Temperature Range: -25°C ~ +60°C (-13°F ~ +140°F)
- Storage Temperature Range: -45°C ~ +80°C (-49°F ~ +176°F)
- Humidity: 90 ~ 95% humidity for 240 hours @ +40°C (+104°F)
- Vibration: 10 ~ 500Hz, amplitude 0.35mm. Acceleration 50m/s²
- Shock: Durability: 1,000m/s²; Malfunction: 150m/s²
- Pollution Degree: 3
- Sealing: Meets IP65 of IEC 60529 Standards at front panel

Installation

- Mounting Torque: 785mN·m
- Soldering Time & Temperature: Manual Soldering: 390°C max for 4 seconds max, 2 cycles

RoHS Compliant:



Standards & Certifications



UL, C-UL (UL508)



EN 60947-5-1, EN 60947-5-5



Optional Accessories Available: Protective Guard, Nameplates With or Without Legends, and Socket Wrench. Contact NKK Switches Sales Dept.