

## F-280U

### Electrical Specifications (@25C)

1. Maximum Power: 120.0 VA
2. Primary: 115V 50/60 Hz
3. Secondary: 60.0VCT @ 2.00 Amps
4. Voltage Regulation: 5 % TYP @ full load to no load
5. Temperature Rise: 35C TYP (45C MAX allowed)

### Description:

The F-280U is part of a series which has a long history of reliable service in the field, made from a proven design and constructed with UL recognized materials.

### Construction:

Wound on a single channel nylon bobbin. Materials are UL recognized, Class B (130° C) rated.

### Safety:

These products are 100% hipot tested with an insulation of 1500V between primary and secondary windings as well as between the primary / secondary windings and the core.

### Dimensions:


Units: In inches

| A     | B     | C     | D     | E     |
|-------|-------|-------|-------|-------|
| 3.750 | 3.125 | 3.125 | 2.500 | 2.625 |

Lead length: 7.0 inches  $\pm$  1 inch

Weight: 5.60 lbs

### Schematic:



Primary: Black to Black

Secondary: Green to Green

**RoHS Compliance:** As of manufacturing date February 2016, all standard products meet the requirements of 2015/863/EU, known as the RoHS 3 initiative.

\* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.

