


# AE-B64-SP3

DIP40/BGA64 specialized adapter for FLASH memory.  
 Device package dimensions: 11.6 x 8.0 x 1.2 mm, 0.8 mm pitch.



Click the programmer model below to get an appropriate list of the devices supported by the adapter:

- [ChipProg+](#)
- [ChipProg-40](#)
- [ChipProg-48, ChipProg-G4](#)

### Adapter Connection Table:

DIP-40	BGA-64	U1, 74HC573	U2, 74HC573	C1, 150pF	C2, 0.1uF
1					
2					
3		11	11	1	
4	D5				
5					
6					
7	C6				
8	E5				
9	C5				
10	C3				
11	D3				
12	E3				
13	F3				
14	D2				
15	E2				
16	F2				
17	G2				
18					
19					

20	G3,J9	1, 10	1, 10	2	2
21	H2				
22	H3				
23	J3	2			
24	K3		2		
25	G4	3			
26	H4		3		
27	K4	4			
28	J4		4		
29	H5	5			
30	K5		5		
31	H6	6			
32	J7		6		
33	K7	7			
34	H7		7		
35	G7	8			
36	K8		8		
37	J8	9			
38	H8		9		
39					
40	J5,J6,J2	20	20		1
			12		
	F9		13		
	D9	12			
	F8	13			
	E8	14			
	D8	15			
	C8	16			
	F7	17			
	E7	18			
	C7	19			
	D7		16		
	E6		15		
	E9		14		
	E4		17		
	F4		18		
	G9		19		