


TECHNICAL DATA SHEET

Part#: 530E-5-USL-040

Cutters - Standoff Shear Small Frame - .040" Standoff - Narrow Jaw
Reduces shock on delicate components and solder connections. Long ergonomic cushioned ESD safe handle.

The 530E-5-USL-040 6" narrow anti-shock shear cutter reduces shock on delicate components and solder connections. The "Stand-Off" keeps the cutting blade from cutting into the solder connections. The tip width is .090". It's recommended cutting capacity is 22 AWG (.25" soft wire). It features a soft cushioned ergonomic Anti-Static grip (10^{10} ohms/sq surface resistivity) with dual leaf springs.

• Precision Level	★★★★★
• Material	Carbon
• Surface Resistivity	10^{10} ohms/sq
• Shape	Straight
• Type of Cut	Shear
• Cutting Capacity	.025"
• Blade Angle	
• Blade Length	.095"
• Body Width	0.42" (10.5mm)
• Body Height	
• OAL	6" (150mm)
• Weight (OZ)	6.2
• UPC	662847013256
• Schedule B	8203.20.60.30
• ECCN	EAR99
• UNSPSC Code	27111511
• Country of Origin	USA
• Group	Small Frame



EXCELTA[®]
CORPORATION

530E-5-USL
Anti-Shock, Standoff
Shear Cutter-Long Handle

A= .640"
B= .100"
C= .095"