

# N800A

## Non-Silicone Thermal Conductive Pad

Non-Silicone Thermal Compound N800A is made of non-silicon resin material. No low molecular siloxane volatilization and low total volatile gas, no electrical contact & pollution problems. N800A is flexible and has great thermal conduction, Low compressive stress and high compressive characteristics can effectively reduce the stress load of components, so that the equipment only needs to bear less mechanical stress, and at the same time, it can have low thermal resistance and high thermal conductivity.

### FEATURES

- / Thermal conductivity:9.0 W/m\*K
- / It's made by non-silicone resin materials
- / Low contact thermal resistance
- / With electrical insulation
- / Outstanding thermal conductivity
- / Applicable to optical and sensitive electric components

### TYPICAL APPLICATION

- / HDDS
- / Optical appliance
- / 5G base station & infrastructure
- / EV electric vehicle

### SPECIFICATIONS

- / Sheet form
- / Die-cut parts



### TYPICAL PROPERTIES

PROPERTY	N800A	TEST METHOD	UNIT
Color	Pink	Visual	-
Surface tack 2-side/1-side	2	-	-
Thickness	Customized	ASTM D374	mm
Density	3.4	ASTM D792	g/cm <sup>3</sup>
Hardness	50	ASTM D2240	Shore OO
Tensile Strength	0.15	ASTM D412	Kgf/cm <sup>2</sup>
Application temperature	-60~125	-	°C
Low molecular Siloxane (D3 to D20 total)	N.D	Gas Chromatography	%
Outgassing CVCM (wt%)	0.0049	By LiPOLY	-
ROHS & REACH	Compliant	-	-
<b>COMPRESSION@1.0mm</b>			
Deflection @10 psi	14	ASTM D5470 modify	%
Deflection @20 psi	35	ASTM D5470 modify	%
Deflection @30 psi	67	ASTM D5470 modify	%
<b>ELECTRICAL</b>			
Dielectric breakdown	8	ASTM D149	KV/mm
Surface resistivity	>10 <sup>11</sup>	ASTM D257	Ohm
Volume resistivity	>10 <sup>10</sup>	ASTM D257	Ohm-m
<b>THERMAL</b>			
Thermal Conductivity	9.0	ASTM D5470	W/m*K
Thermal impedance@10 psi	0.238	ASTM D5470	°C-in <sup>2</sup> / W
Thermal impedance@20 psi	0.166	ASTM D5470	°C-in <sup>2</sup> / W
Thermal impedance@30 psi	0.102	ASTM D5470	°C-in <sup>2</sup> / W

The chemical formula indicates that if Cyclic polydimethylsilox-ane (HO-[Si(CH3)2O]n-H) is non-reaction, it's volatile anytime and everywhere. For example, when the electric products which has been put in a confined space, the volatile of low-molecular-weight silox-anes will makes the elecetic products uncontacted.

### Thermal Resistance vs. Pressure vs. Deflection

